Submit I Copy To Appropriate District Office	State of New Mexico		Form C-103		
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		Revised August 1, 2011 WELL API NO.		
<u>District II</u> - (575) 748-1283	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		30-025-41364		
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178			5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505		STA		
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa 1 6, 14141 67 303		39652	& Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Na	ame or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Pottlo	Battle	
PROPOSALS.)			8. Well Number 1H		
 Type of Well: Oil Well Name of Operator 	Gas Well Other	J600 000	9. OGRID Number		
BC Operating, Inc.	11	2.4.2014	160825		
3. Address of Operator	JUL 24 2014		10. Pool name or Wildcat		
P.O. Box 50820 Midland, Texas 79			WC-025 G-06 S213326D; Bone Spring		
4. Well Location RECEIVED					
Unit Letter A: 160 feet from the North line and 360 feet from the East line					
Section 34	Township 21S R	ange 33E	NMPM	County Lea	
The state of the s	11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3702' GL				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR		☐ ALTERING CASING ☐	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DR			
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMEN	T JOB		
DOWNHOLE COMMINGLE					
OTHER:		OTHER:			
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date					
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of					
proposed completion or recompletion.					
07/07/2014					
07/06/2014: Ran 36 joints of 13 3/8" 54.5# J-55 STC casing from 0' to 1670'. Cemented with Lead 1010 sx Class C/288 bbls @ 13.7 ppg with					
Yield of 1.6 and Tailed with 560 sx/130 bbls @ 14.8 ppg with yield of 1.3. Dropped plug & displaced with 251 bbls brine water. 189					
bbls displacement had cement to surface & circulated 218 sx. Bumped plug 500 psi over, checked floats - held RD Trican Cementers.					
•					
		•			
Spud Date: 07/01/201	4 Rig Release	Data:			
Spud Date.	Rig Reicase	Date.			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
\circ					
SIGNATURE Yam Strucks TITLE Regulatory Analyst DATE 07/07/2014					
TO COLORS DISTRIBUTE AND COLORS DISTRIBUTE AND COLORS					
Type or print name Pam Stevens E-mail address: pstevens@bcoperating.com PHONE: 432-684-9696					
For State Use Only Petroleum Engineer					
APPROVED BY: DATE 1/19/14					
Conditions of Approval (if any):					

AUG 0 5 2014

