Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

CHG Loc

RBDMS

CSNG_

OCD Hobbs)
-----------	---

FORM APPROVED

FEB 1 7 2015

OMB No. 1004-0137 Expires: July 31, 2010

NMNM86172

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			111111111111111111111111111111111111111	6. If Indian, Allottee or Tribe Name		
			RECEIVED Allotte			
SUBMIT IN TRIPLICATE – Other instructions on page 2.			7. If Unit of CA/Ag	7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well						
Oil Well Gas Well Other				8. Well Name and No. APPLESEED SWD FEDERAL #2		
2. Name of Operator CHEVRON U.S.A. INC.			9. API Well No. 30-025-03352	9. API Well No. 30-025-03352		
3a, Address 15 SMITH ROAD MIDLAND,		3b. Phone No. (include area code) Bob Holden 432-234-7325	10. Field and Pool of SWD; YATES - 7	or Exploratory Area RIVERS		
Location of Well (Footage, Sec., T.,R.,M., or Survey Description) 980 FSL, 8 660 FEL, UL: 1, SEC 17, T-20S, R-35E			11. Country or Parish, State LEA COUNTY, NEW MEXICO			
		3693 GL				
	CK THE APPROPRIATE BO	X(ES) TO INDICATE NATURE OF	·	THER DATA		
TYPE OF SUBMISSION		TYPE	OF ACTION	CTION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity		
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily Abandon	Other		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal			
8-5/8" 24# @ 305' 225 sks of Class 5-1/2" 17# @ 4158' w/ 1200 sks of Perfs 4520' -4829' Csg leak @ 395 1. MIRUWSU. NDWH. NUBOPE 2. Tag Retiveable CIBP @ 3869" v 3. Pressure Test casing to 500 psi 4. Set Plug @ 3600' - 3400' wl 20' s 5. Set Plug @ 2150' - 1950' w/20' s 6. Perf & Circulate & Verify 400' - \$ 7. Cut off wellhead and anchors 3'	cmt Hole size 7-7/8" TOC C 2' - 3974' w/25 sks of C cement and record/report findings sks of Class C cmt WOC & T ks of Class C cmt WOC & T Surface, wl 100 sks of Class	FAG (bottom-Salt) 25 5 FAG (Top of Salt) 25 5 FC, (covers Shoe)	COND	TTACHED FOR ITIONS OF APPROVAL CLAMATION PROCEDURE		
Selow ground	Der Hole M	Carker Registres	d Read	ATTACHED		
<i>'</i> ' / '/)	true and correct. Name (Printed			crai may of ne		
Robert Holden	4/1/	Title Operation Ag	gent			
Signature	1 11	Date 01/20/2015				
	/ THIS SPACE	FOR FEDERAL OR STATI	E OFFICE USE			
Approved by Conditions of approved, it any, are attached the applicant holds legal or equitable ntitle the applicany to conduct operations		not warrant or certify	P <u>E</u> T	Date 2-3-15		
_	NT to PA PM.	for any person knowingly and wi urisdiction.	illfully to make to any departm	nent or agency of the United States any false,		
P&A NR DHC COMP				ምምስ ቁ ማ ባበ ነ ቬ		

MUB/OCD 2/16/2015

Chevron U.S.A. Inc. Wellbore Diagram: ASD SWD F 2



Proposed

[Lease] OEU EUNICE FMT [Well No.] APPLESED SWD FEDERAL 2 SWD 2 [Field] BURTON FLAT [Location] 1980FSL660FEL [Sec.] N/A [Blk] [Survey] N/A [County] Lea [St.] New Mexico [Refno] FA4504 [API] 3002503352 [Cost Center] UCRD3L01X [Section] E035 [Township] 17 [Range] S020 [Current Status] ACTIVE [Dead Man Anchors Test Date] NONE [Directions]

Surface Casing (Top-Bottom Depth) Desc @(11-305) Wellbore Hole OD-12.2500-@(11-305) Cement (behind Casing)-@(11-305) Armco-95 8.625 OD/ 32.00# Round Long 7.921 ID 7.796 Drift-Production Casing (Top-Bottom Depth) Desc @(305-4158) Wellbore Hole OD- 7.8750-@(11-4130) Cement (behind Casing)-@(990-1000) Plug - Sand on Top of Bridge Plug-@(1000-1003) Retrieveable Bridge Plug (Unknown Size)-@(3869-3872) Retrieveable Bridge Plug (Unknown Size)-@(3932-4038) Producing Interval (Completion)-@(3932-4038) Perforations-Open 1-4130) J-55 5.500 CD/ 15.50# Unknown Thread 4.950 ID 4.825 Drift-@(4081-4130) Plug Back (unknown type)-Remove Retiveable CIBP @ 3869 wl 25 shs of Class C moe & TAL


[Ground Elevation (MSL)] 0.00 [Spud Date] 07/10/1970 [Compl. Date] 07/20/1960 [Well Depth Datum] Kelly Bushing [Elevation (MSL)] 3710.00 [Correction Factor] 11.00 [Last Updated by] fitecl [Date] 06/09/2014 [null] null [null] null

Chevron U.S.A. Inc. Wellbore Diagram: ASD SWD F 2



CURRENT

[Lease] OEU EUNICE FMT [Well No.] APPLESEED SWD FEDERAL 2 SWD 2 [Field] BURTON FLAT [Location] 1980FSL660FEL [Sec.] N/A [Blk] [Survey] N/A [County] Lea [St.] New Mexico [Refno] FA4504 [API] 3002503352 [Cost Center] UCRD3L01X [Section] E035 [Township] 17 [Range] S020 [Current Status] ACTIVE [Dead Man Anchors Test Date] NONE [Directions]



[Ground Elevation (MSL)] 0.00 [Spud Date] 07/10/1970 [Compl. Date] 07/20/1960 [Well Depth Datum] Kelly Bushing [Elevation (MSL)] 3710.00 [Correction Factor] 11.00 [Last Updated by] fited [Date] 06/09/2014 [null] [null] null [null] null [null] null [null]

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>minety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within tem (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged</u>.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Duncan Whitlock Environmental Protection Specialist 575-234-5926

Linda Denniston Environmental Protection Specialist 575-234-5974 Cody Layton Supervisory Multi Resources 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Jeffery Robertson Natural Resource Specialist 575-234-2230

Solomon Hughes Natural Resource Specialist 575-234-5951