

Submitt 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 May 27, 2004

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-37074
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-623
7. Lease Name or Unit Agreement Name Perch State
8. Well Number 2
9. OGRID Number 013837
10. Pool name or Wildcat Grayburg Jackson SR Q G SA

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Mack Energy Corporation

3. Address of Operator
P. O. Box 960 Artesia, NM 88211-0960

4. Well Location
 Unit Letter A 330 feet from the North line and 990 feet from the East line
 Section 30 Township 16S Range 32E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4359' GR

Pit or Below-grade Tank Application or Closure

Pit type Plugging Depth Groundwater 210' Distance from nearest fresh water well 1000' Distance from nearest surface water 1000'

Pit Liner Thickness: 12 mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data


NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL. <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: _____ <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hours prior to starting plugging operations.
2. Set CIBP @ 3604' w/ 35' cement cap above perfs at 3704' and circ hole with mud.
3. Set 35 sx cement plug 50' above and below 8 5/8" csg from 470' - 370'. - TAG
4. Set 10 sx surface plug.
5. Install dry hole marker.

→ SPOT 25JX F/1100' - 762' (T.O.S)

**THE OIL CONSERVATION DIVISION MUST
 BE NOTIFIED 24 HOURS PRIOR TO THE
 BEGINNING OF PLUGGING OPERATIONS.**



I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan


SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 11/7/2005
 Type or print name Jerry W. Sherrell E-mail address: jerrys@mackenergycorp.com Telephone No. (505)748-1288
 For State Use Only

APPROVED BY: Hary W. Wink FIELD REPRESENTATIVE II/STAFF MANAGER DATE _____
 Conditions of Approval (if any) _____

NOV 09 2005

MACK ENERGY CORPORATION
Perch State #2
Sec 30 T16S R32E 330FNL 990FEL

BEFORE




8 5/8" 24# @ 420' Circ Cmt

Perfs 3704'-4153'

4 1/2" 11.6# @ 4250' Circ Cmt

AFTER



10sk plug surface

8 5/8" 24# @ 420' Circ Cmt

Set CIBP 3604' w35'cmt cap

Perfs 3704'-4153'

4 1/2" 11.6# @ 4250' Circ Cmt

- 1 Notify OCD 24hrs of plugging
- 2 Set CIBP @3604' w/35'cmt cap above perfs at 3704" and circ hole with mud
- 3 Set 35 sk cmt plug 50' above and below csg 8 5/8" From 470-370'
- 4 Set 10sk surface plug
- 5 Install dry hole marker