Office	w Mexico	Form C-103	
District I – (575) 393-6161 Energy, Minerals and	Natural Resources	Revised July 18, 2013	
1625 N. French Dr., Hobbs, NM 88240  District II – (575) 748-1283  OIL CONSERVAT		WELL API NO.	
811 S. First St., Artesia, NM 88210 OIL CONSERVAT	TION DIVISION	30-025-33178	
811 S. First St., Artesia, NM 88210  District III – (505) 334-6178  1000 Rio Brazos Rd., Aztec, NM 87410 MAY  District IV – (505) 476-3460  Santa Fe, N	Francis Dr.	5. Indicate Type of Lease STATE FEE X	
1000 Rio Brazos Rd., Aztec, NM 87410 MA1  District IV – (505) 476-3460  Santa Fe, N	M 87505	6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505		o. State on a das Bease No.	
SUNDRY NOTICES AND REPORTS ON W		7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-		SHAW 15	
PROPOSALS.)		8. Well Number	
1. Type of Well: Oil Well X Gas Well Other		2	
2. Name of Operator CHEVRON U.S.A. INC.		9. OGRID Number 4323	
<ul><li>3. Address of Operator</li><li>15 SMITH RD. MIDLAND, TX. 79705</li></ul>		Pool name or Wildcat     HUMBLE CITY-STRAWN	
4. Well Location GPS Y- LAT 32.83611 X-LONG -103.23775			
Unit Letter G: 2,100 feet from the NORTH line and 2,310 feet from the EAST line			
Section 15 Township 17-S Range 37-E NMPM County LEA			
11. Elevation (Show whether			
3,756' GR			
<ol><li>Check Appropriate Box to Indica</li></ol>	ate Nature of Notice,	Report or Other Data	
NOTICE OF IN	SUB	SEQUENT REPORT OF:	
TEMPORARILY ABANDON P&A NR CASING CASING CASING CEMENT ION CASING			
PULL OR ALTER CASING P&A R	CASING/CEMEN		
DOWNHOLE COMMINGLE			
CLOSED-LOOP SYSTEM			
OTHER:	OTHER:		
<ol> <li>Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 19.15.7.14 N</li> </ol>			
proposed completion or recompletion. 13 3/8" 48# @			
5 ½" 20# @ 11,720' TOC 10,750' CALC, PERFS 11,			
04/27-29/16 MI RIG & CMT EQUIP. ND & NU BOP, POOH W/			
	05/02/16 RIH TO 11,300' WELL ON VACUUM, POOH, MARK WHITAKER W/ NMOCD OK SETTING CIBP @ 11,235'.		
05/03/16 RIH SET CIBP @ 11,235', MIX & SPOT 65 SX CL "H" CMT FROM 11,235'-10,641'.			
05/04/16 RIH TAG CIRP @ 11 235' NO CMT MAXEY BROW	" CMT FROM 11,235'-1	0,641'.	
05/04/16 RIH TAG CIBP @ 11,235', NO CMT. MAXEY BROW TOTAL OF 48' OF CL "H" CMT. TOC @ 11.087'.	" CMT FROM 11,235'-1	0,641'.	
05/04/16 RIH TAG CIBP @ 11,235', NO CMT. MAXEY BROW TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO	" CMT FROM 11,235'-1 N W/ NMOCD OK CIB	0,641'. P @ 11,135', MADE 3 DUMP BAIL RUNS	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO	" CMT FROM 11,235'-I N W/ NMOCD OK CIB T 65 SX CL "H" CMT 1 P & SPOT, MIX & SPO	0,641'. P @ 11,135', MADE 3 DUMP BAIL RUNS 1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL.	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK	"CMT FROM 11,235'-I'N W/ NMOCD OK CIB TT 65 SX CL "H" CMT 1 IP & SPOT, MIX & SPO ER OK DROP,MIX & S	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT	"CMT FROM 11,235'-1" N W/ NMOCD OK CIB T 65 SX CL "H" CMT 1 P & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6,	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M.	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9	" CMT FROM 11,235'-1" N W/ NMOCD OK CIB TO 65 SX CL "H" CMT 1 P & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 050', PERF @ 4,525', M	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'.	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2,	" CMT FROM 11,235'-1" N W/ NMOCD OK CIB TO 65 SX CL "H" CMT 1 P & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 950', PERF @ 4,525', M 700', TAG @ 2,636', PE	10,641'. P @ 11,135', MADE 3 DUMP BAIL RUNS 1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'.	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9	"CMT FROM 11,235'-1" N W/NMOCD OK CIB TO 65 SX CL "H" CMT 1 P & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 950', PERF @ 4,525', M 700', TAG @ 2,636', PE T FROM 500' BACK TO	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT	"CMT FROM 11,235'-1" N W/NMOCD OK CIB TO 65 SX CL "H" CMT 1 P & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 950', PERF @ 4,525', M 700', TAG @ 2,636', PE T FROM 500' BACK TO	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE	" CMT FROM 11,235'-1" N W/ NMOCD OK CIB TO W/ NMOCD OK CIB TO 65 SX CL "H" CMT 11 P & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 050', PERF @ 4,525', M 700', TAG @ 2,636', PE TO FROM 500' BACK TO ELD ON DRY HOLE MA	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION.  ALL CEMENT PLUGS CLASS "H & C", W/ CLOSED LOO	"CMT FROM 11,235'-1" NW/NMOCD OK CIB TO W/NMOCD OK CIB TO 65 SX CL "H" CMT 1 TO & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 050', PERF @ 4,525', M 700', TAG @ 2,636', PE TO FROM 500' BACK TO ELD ON DRY HOLE MA	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION.	"CMT FROM 11,235'-1" NW/NMOCD OK CIB TO W/NMOCD OK CIB TO 65 SX CL "H" CMT 1 TO & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 050', PERF @ 4,525', M 700', TAG @ 2,636', PE TO FROM 500' BACK TO ELD ON DRY HOLE MA	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION.  ALL CEMENT PLUGS CLASS "H & C", W/ CLOSED LOO	"CMT FROM 11,235'-1" NW/NMOCD OK CIB TO W/NMOCD OK CIB TO 65 SX CL "H" CMT 1 TO & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 050', PERF @ 4,525', M 700', TAG @ 2,636', PE TO FROM 500' BACK TO ELD ON DRY HOLE MA	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'. 05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION.  ALL CEMENT PLUGS CLASS "H & C", W/ CLOSED LOO	"CMT FROM 11,235'-1" NW/NMOCD OK CIBOT 65 SX CL "H" CMT 12 P & SPOT, MIX & SPOER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 250', PERF @ 4,525', M 700', TAG @ 2,636', PET FROM 500' BACK TO ELD ON DRY HOLE MARSE Date:	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. D SURFACE ON BOTH STRINGS. CUT ALL ARKER AS PER RULE 19.15.7.14. OF	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'.  05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION. ALL CEMENT PLUGS CLASS "H & C", W/ CLOSED LOO  Spud Date:  Rig Relea	"CMT FROM 11,235'-1" NW/NMOCD OK CIBOT 65 SX CL "H" CMT 11 P & SPOT, MIX & SPOTER OK DROP,MIX & STOTE	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. IX SURFACE ON BOTH STRINGS. CUT ALL ARKER AS PER RULE 19.15.7.14. OF	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'.  05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION. ALL CEMENT PLUGS CLASS "H & C", W/ CLOSED LOO  Spud Date:  Rig Relea  I hereby certify that the information above is true and complete to	"CMT FROM 11,235'-1" NW/NMOCD OK CIB TO 65 SX CL "H" CMT 11 P & SPOT, MIX & SPO ER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 050', PERF @ 4,525', M 700', TAG @ 2,636', PE T FROM 500' BACK TO ELD ON DRY HOLE MA P SYSTEM.  The best of my knowledge Agent for Chevron	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL ARKER AS PER RULE 19.15.7.14. OF	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'.  05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION. ALL CEMENT PLUGS CLASS "H & C", W/ CLOSED LOO  Spud Date:  Rig Relea  Title Type or print name  Monty L. McCarver  E-mail address:  I	"CMT FROM 11,235'-1" N W/ NMOCD OK CIBOT 65 SX CL "H" CMT 11 P & SPOT, MIX & SPOER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 250', PERF @ 4,525', M 700', TAG @ 2,636', PERF CELD ON DRY HOLE MARKED ON DRY HO	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. D SURFACE ON BOTH STRINGS. CUT ALL ARKER AS PER RULE 19.15.7.14. OF	
TOTAL OF 48' OF CL "H" CMT, TOC @ 11,087'.  05/05/16 RIH TAG @ 11,060', CIR BRINE & GEL, MIX & SPO 05/06/16 PERF @ 9,800', NO SQZ, BILL W/ NMOCD OK DRO 05/09/16 TAG @ 9,387', PERF @ 8,600', NO SQZ M. WHITAK 05/10/16 TAG @ 8,440' & TEST 600 PSI GOOD, MIX & SPOT WHITAKER OK DROP, MIX & SPOT 30 SX CL "C" 5,275'-4,9 05/11/16 TAG @ 4,166', PERF & SQZ 200 SX CL "C" 3,400'-2, 05/12/16 TAG @ 1,801', PERF & CIR 180 SX CL "C" CEMENT CASING & ANCHORS & REMOVED 3' BELOW GRADE. WE NMAC, CLEAN LOCATION. ALL CEMENT PLUGS CLASS "H & C", W/ CLOSED LOO  Spud Date:  Rig Relea  Title Type or print name  Monty L. McCarver  E-mail address:  I	"CMT FROM 11,235'-1" N W/ NMOCD OK CIBOT 65 SX CL "H" CMT 11 P & SPOT, MIX & SPOER OK DROP,MIX & S 55 SX CL "H" 7,076'-6, 250', PERF @ 4,525', M 700', TAG @ 2,636', PERF CELD ON DRY HOLE MARKED ON DRY HO	1,060'-10,422', TAG @ 10,374'. T 65 SX CL "H" 9,850'-9,332'. SQZ 1 BBL. POT 50 SX CL "H" 8,650'-8,175' SQZ 2 BBL 491', PERF @ 5,225', NO SQZ M. IX & SQZ 110 SX CL "C" 4,525'-4,175'. ERF & CIR 100 SX CL "C" 2,200'-1,875'. SURFACE ON BOTH STRINGS. CUT ALL ARKER AS PER RULE 19.15.7.14. OF	