Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources	Revised July 18, 2013 WELL API NO.
District II – (575) 748-1283	B OIL CONSERVATION DIVISION	30-025-05637
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460	NOV 21 2016 Santa Fe, NM 87505	STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	10121	B-1382-5
87505 SUNDRY NOTI	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPODIFFERENT RESERVOIR. USE "APPLIC	SALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A CATION FOR PERMIT" (FORM C-101) FOR SUCH	North Monument G/SA Unit (302708)
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well Other	8. Well Number 016
Name of Operator Apache Corporation		9. OGRID Number 873
3. Address of Operator	· · · · · · · · · · · · · · · · · · ·	10. Pool name or Wildcat
303 Veterans Airpark Lane, Suite 10	000 Midland, TX 79705	Eunice Mon; Grayburg - SA (23000)
4. Well Location	660 feet from the Southe line and	660 feet from the East line
Unit Letter :_ Section 18	feet from the Southe line and Township 19S Range 37E	NMPM County Lea
Section 18	11. Elevation (Show whether DR, RKB, RT, GR,	
	3701 GL	
12. Check A	Appropriate Box to Indicate Nature of Notice	ce, Report or Other Data
NOTICE OF IN		UBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL W	
TEMPORARILY ABANDON DULL OR ALTER CASING	CHANGE PLANS COMMENCE MULTIPLE COMPL CASING/CEM	DRILLING OPNS. P AND A
DOWNHOLE COMMINGLE	MIDETIFEE COMPE	LINI JOB
CLOSED-LOOP SYSTEM		
OTHER:	OTHER: Perf	
	leted operations. (Clearly state all pertinent details,	
of starting any proposed wo	ork). SEE RULE 19.15.7.14 NMAC. For Multiple	Completions: Attach wellbore diagram of
Apache has performed the following w	•	
11/07/2016 RU Capitan WL. RIH w/ 3 1/8" slick guns & perf: 3768-88, 3819-29 @ 4 SPF, 60 Degree Phase. Total 120 Holes, RD Capitan. Set RBP @ 3835' PU & Set PKR @ 3674'. RU Cudd. Acidize Grayburg: 3768-3829. Pump 3000 Gal 15% Grayburg blend. Drop 200 ball sealers evenly. Good ball action. RD Cudd.		
11/08/2016 Pull PKR & Plug. Run pro	duction tubing.	
11/09/2016 Run rods. RDMO.	_	
11/09/2010 Rull Tods. RDIMO.		
Spud Date:	Rig Release Date:	
		The state of the s
I hereby certify that the information	above is true and complete to the best of my knowl	edge and belief.
\cap \cup		
SIGNATURE Stabel to	TITLE Regulatory Analyst	DATE 11/15/2016
Type or print name Isabel Hudson	E-mail address: Isabel.hudson@	@apachecorp.com PHONE: (432) 818-1142
For State Use Only		1.
APPROVED BY:	TITLE Petroleum	Engineer DATE 1/26/16
Conditions of Approval (if any):		.,, ///