

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-03872
1. Type of Well: Oil Well Gas Well Other X INJECTION		5. Indicate Type of Lease STATE X FEE
2. Name of Operator CHEVRON U.S.A. INC.		6. State Oil & Gas Lease No.
3. Address of Operator 6301 DEAUVILLE BLVD, MIDLAND, TX. 79706 RM N3002		7. Lease Name or Unit Agreement Name WEST LOVINGTON UNIT
4. Well Location GPS Y- LAT 32.858370 X-LONG -103.36120 Unit Letter N : 660 feet from the SOUTH line and 1980 feet from the WEST line Section 4 Township 17-S Range 36-E NMPM County LEA		8. Well Number 35
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 241333
		10. Pool name or Wildcat LOVINGTON UPPER SA WEST

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INT

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

INT TO PA

P&A NR **pm. x**
P&A R

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A **X**
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06/14-15/17 MI & RU, PRESSURE ON WELL, SET PLUG IN PACKER PROFILE NIPPLE, LEAKING. WILL PERF & KILL.

SET CIBP
06/16/17 **PERF** @ 4,610', PUMP 13# WBM, NDWH, NU BOP, RELEASE ON /OFF TOOL, TEST CSG 500# GOOD, RIH SET CIBP @ 4,609', GATOR TOOL PERF @ 3,150' & 2,013'.

06/17/17 RIH TO CIBP, CIR MLF, MIX & SPOT 25 SX CL "C" CMT FROM 4,609' - 4,368', UNABLE TO PUMP INTO PERFS @ 3,150', MARK WHITAKER OK DROP 50', MIX & SPOT 55 SX CMT FROM 3,200' - 2,700', WOC & TAG @ 2,667', EST. INJ. RATE ON 2,013' PERFS, MIX & SQZ 60 SX CL "C" CMT FROM 2,013' - 1,700'.

06/18/17 RIH TAG @ 1,790', PERF @ 1,100', MIX & CIR 120 SX CL "C" CMT FROM 1,100' - 900', GOOD CIR ON BOTH 5 1/2" & 8 5/8", WOC & TAG @ 896', PERF @ 375', MIX & CIR 300 SX CL "C" CMT FROM 375' BACK TO SURFACE ON ALL THREE STRINGS OF CSG. CUT ALL CASING & ANCHORS & REMOVED 3' BELOW GRADE. WELD ON DRY HOLE MARKER AS PER RULE 19.15.7.14. OF NMAC, CLEAN LOCATION. TURN OVER TO RECLAMATION.

ALL CEMENT PLUGS CLASS "C", W/ CLOSED LOOP SYSTEM.
CA BOND; 0329

Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.
Restoration Due By **06-17-2018**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE **Monty L. McCarver** TITLE **Agent for Chevron** DATE **06/20/17**
Type or print name **Monty L. McCarver** E-mail address: **monty.mccarver@cjes.com** PHONE: **713-325-6288**

For State Use Only
APPROVED BY: **Mark Whitaker** TITLE **P.E.S.** DATE **06/22/2017**
Conditions of Approval (if any):