Form 3160 -3 (March 2012)

HOBBS OCD UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SEP 11 2017

FORM APPROVED OMB No. 1004-0137 Expires October 31, 2014

Lease Serial No. NMLC063228

6. If Indian, Allotee or Tribe Name

APPLICATION FOR PERMIT TO DE	RILL OR	REENTER	VED	6. If Indian, Allotee	of Tribe I	vame		
la. Type of work:		110		7. If Unit or CA Agre	ement, Na	me and No.		
lb. Type of Well: Oil Well Gas Well Other	Sing	gle Zone Multip	le Zone	8. Lease Name and V TRISTE DRAW 25		AL CO 14H		
2. Name of Operator CIMAREX ENERGY COMPANY (2.1)	15099	-)		9. API Well No.	5-	44002		
	o. Phone No. 432)620-19	(include area code)		10. Field and Pool, or F BONE SPRING / T		10-		
Location of Well (Report location clearly and in accordance with any Statement SESW / 560 FSL / 2390 FWL / LAT 32.269997 /	/ LONG -10	03.629144		11. Sec., T. R. M. or B SEC 25 / T23S / R3				
At proposed prod. zone NENW / 330 FNL / 2110 FWL / LAT 3 14. Distance in miles and direction from nearest town or post office*	32.282075	/ LONG -103.6300	58	12. County or Parish		13. State		
27.4 miles				LEA		NM		
location to nearest FGO foot	16. No. of ac 1600	res in lease	17. Spacin 160	ng Unit dedicated to this well				
to nearest well, drilling, completed, 20 feet applied for, on this lease, ft.	well, drilling, completed, 20 feet or, on this lease, ft. 9450 feet / 13692 feet FED:							
	2 Approxim 12/01/2017	nate date work will star	t*	23. Estimated duration 30 days	n			
	24. Attacl	hments				_		
The following, completed in accordance with the requirements of Onshore O 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lar SUPO must be filed with the appropriate Forest Service Office).		4. Bond to cover the Item 20 above).5. Operator certification	ne operatio	ns unless covered by an				
25. Signature		(Printed/Typed)	10)500 7		Date	20.17		
(Electronic Submission) Title Regulatory Analyst	Aricka	Easterling / Ph: (9	918)560-7	060	03/31/2	2017		
Approved by (Signature) (Electronic Submission)		(Printed/Typed) Layton / Ph: (575)2	34-5959		Date 08/18/2	2017		
Title Supervisor Multiple Resources	Office CARL	SBAD						
Application approval does not warrant or certify that the applicant holds le conduct operations thereon. Conditions of approval, if any, are attached.	egal or equita	able title to those right	ts in the sub	ject lease which would e	ntitle the a	pplicant to		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crim States any false, fictitious or fraudulent statements or representations as to a	ne for any per any matter wi	rson knowingly and within its jurisdiction.	villfully to n	nake to any department o	r agency	of the United		
(Continued on page 2)			OVC	*(Instruge)		s on page 2)		
	n wit	H CONDITI	NID	09/111	11/			





U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

erator Certification Data Report

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filling of false statements.

NAME: Aricka Easterling

Signed on: 03/31/2017

Zip: 74103

Zip:

Title: Regulatory Analyst

Street Address: 202 S. Cheyenne Ave, Ste 1000

City: Tulsa

State: OK

Phone: (918)560-7060

Email address: aeasterling@cimarex.com

HOBBS OCD

SEP 11 2017

RECEIVED

Field Representative

Street Address:

Representative Name:

City:

State:

Phone:

Email address:



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Application Data Report

09/05/2017

APD ID: 10400012840

Operator Name: CIMAREX ENERGY COMPANY

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Type: OIL WELL

Submission Date: 03/31/2017

Well Number: 14H

Well Work Type: Drill

Highlighted data reflects the most recent changes

Show Final Text

Section 1 - General

10400012840 APD ID:

Tie to previous NOS? 10400011555

Submission Date: 03/31/2017

BLM Office: CARLSBAD

User: Aricka Easterling

Title: Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMLC063228

Lease Acres: 1600

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: CIMAREX ENERGY COMPANY

Operator letter of designation:

Operator Info

Operator Organization Name: CIMAREX ENERGY COMPANY

Operator Address: 202 S. Cheyenne Ave., Ste 1000

Zip: 74103

Operator PO Box:

Operator City: Tulsa

State: OK

Operator Phone: (432)620-1936

Operator Internet Address: tstathem@cimarex.com

Section 2 - Well Information

Well in Master Development Plan? NO

Mater Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Number: 14H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: BONE SPRING

Pool Name: TRISTE DRAW

BONE SPRING

Is the proposed well in an area containing other mineral resources? POTASH

Page 1 of 3

Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H

Describe other minerals:

Is the proposed well in a Helium production area? N Use Existing Well Pad? NO

New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:

Number: 2

Well Class: HORIZONTAL

TRISTE DRAW SUPERPAD 2 Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL Describe Well Type:

Well sub-Type: EXPLORATORY (WILDCAT)

Describe sub-type:

Distance to town: 27.4 Miles

Distance to nearest well: 20 FT

Distance to lease line: 560 FT

Reservoir well spacing assigned acres Measurement: 160 Acres

Triste_Draw_25_Fed_Com_14H_C102_Plat_03-31-2017.pdf

Well work start Date: 12/01/2017

Duration: 30 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number:

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL Leg #1	560	FSL	239 0	FWL	238	32E	25	Aliquot SESW	32.26999 7	- 103.6291 44	LEA		NEW MEXI CO	F	NMLC0 63228	369 0	0	0
KOP Leg #1	560	FSL	239 0	FWL	23S	32E	25	Aliquot SESW	32.26999 7	- 103.6291 44	LEA		NEW MEXI CO	F	NMLC0 63228	- 525 4	894 4	894 4
PPP Leg #1	560	FSL	239 0	FWL	23S	32E	25	Aliquot SESW	32.26999 7	- 103.6291 44	LEA	1	NEW MEXI CO	F	NMLC0 63228	- 514 0	883 0	883 0

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Number: 14H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	DVT
EXIT Leg #1	330	FNL	211 0	FWL	23S	32E	25	Aliquot NENW	32.28207 5	- 103.6300 58	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 86154	- 576 0	136 92	945 0
BHL Leg #1	330	FNL	211	FWL	23S	32E	25	Aliquot NENW	32.28207 5	- 103.6300 58	LEA	NEW MEXI CO		F	NMNM 86154	- 576 0	136 92	945 0



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

09/05/2017

APD ID: 10400012840

Submission Date: 03/31/2017

Highlighted data reflects the most recent changes

Well Name: TRISTE DRAW 25 FEDERAL COM

Operator Name: CIMAREX ENERGY COMPANY

Well Number: 14H

Show Final Text

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation	Formation Name	Elevation	True Vertical	计图像数据的数据	Lithologies	Mineral Resources	Producing Formation
17746	RUSTLER	3690	Depth 1240	Depth 1240	Lithologies	USEABLE WATER	No
18574	SALADO	1960	1730	1730		NONE	No
17722	BASE OF SALT	-1110	4800	4800		NONE	No
17760	DELAWARE SAND	-1340	5030	5030		NONE	No
17713	BRUSHY CANYON	-3670	7360	7360		NATURAL GAS,OIL	No
17688	BONE SPRING	-5140	8830	8830		NATURAL GAS,OIL	Yes
15338	BONE SPRING 1ST	-6350	10040	10040		NATURAL GAS,OIL	Yes
.5500	2020. 14.10 701		.5310	,5510			, 50

Section 2 - Blowout Prevention

Pressure Rating (PSI): 2M

Rating Depth: 1270

Equipment: Exhibit "E-1". A BOP consisting of three rams, including one blind ram and two pipe rams and one annular preventer. An accumulator that meets the requirements in Onshore Order #2 for the pressure rating of the BOP stack. A rotating head may be installed as needed. A Kelly clock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor.

Requesting Variance? YES

Variance request: Co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached (Please see Exhibit F, F-1, F-2, F-3). The hose is not required by the manufacturer to be anchored. In the event the specific hose is not available, one of equal or higher rating will be used. Variance to include Hammer Union connections on lines downstream of the buffer tank only.

Testing Procedure: BOP's will be tested by an independent service company. The ram preventers, choke manifold, and safety valves will be tested as follows: On the surface casing, pressure tests will be made to 250 psi low and 2000 psi high. On the intermediate casing, pressure tests will be made to 250 psi low and 3000 psi high. The Annular Preventer will be tested to 250 psi low and 1000 psi high on the surface casing and 250 psi low and 1500 psi high on the intermediate casing. The System may be upgraded to a higher pressure but still tested to the working pressures listed. If the system is upgraded all the components installed will be functional and tested.

Choke Diagram Attachment:

Triste_Draw_25_Fed_Com_14H_Choke_2M3M_03-31-2017.pdf

Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H

Triste Draw 25 Fed Com 14H Choke 2M3M 03-31-2017.pdf

BOP Diagram Attachment:

Triste Draw 25 Fed Com 14H BOP 2M 03-31-2017.pdf

Pressure Rating (PSI): 3M

Rating Depth: 5010

Equipment: Exhibit "E-1". A BOP consisting of three rams, including one blind ram and two pipe rams and one annular preventer. An accumulator that meets the requirements in Onshore Order #2 for the pressure rating of the BOP stack. A rotating head may be installed as needed. A Kelly clock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor.

Requesting Variance? YES

Variance request: Co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached (Please see Exhibit F, F-1, F-2, F-3). The hose is not required by the manufacturer to be anchored. In the event the specific hose is not available, one of equal or higher rating will be used. Variance to include Hammer Union connections on lines downstream of the buffer tank only.

Testing Procedure: BOP's will be tested by an independent service company. The ram preventers, choke manifold, and safety valves will be tested as follows: On the surface casing, pressure tests will be made to 250 psi low and 2000 psi high. On the intermediate casing, pressure tests will be made to 250 psi low and 3000 psi high. The Annular Preventer will be tested to 250 psi low and 1000 psi high on the surface casing and 250 psi low and 1500 psi high on the intermediate casing. The System may be upgraded to a higher pressure but still tested to the working pressures listed. If the system is upgraded all the components installed will be functional and tested.

Choke Diagram Attachment:

Triste_Draw_25_Fed_Com_14H_Choke_2M3M_03-31-2017.pdf

BOP Diagram Attachment:

Triste_Draw_25_Fed_Com_14H_BOP_3M_03-31-2017.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1270	0	1270	0	1270	1270	OTH ER	48	STC	1.27	2.98	BUOY	5.28	BUOY	5.28
2		12.2 5	9.625	NEW	API	N	0	5010	0	5010	0	5010	5010	J-55	40	LTC	1.54	1.49	BUOY	2.59	BUOY	2.59
3	PRODUCTI ON	8.75	5.5	NEW	API	N	0	8944	0	8944	0	8944	8944	L-80	17	LTC	1.47	1.81	BUOY	2.1	BUOY	2.1
4	PRODUCTI ON	8.75	5.5	NEW	API	N	8944	13692	8944	13692	8944	13692	4748	L-80	17	BUTT	1.39	1.71	BUOY	46.1 5	BUOY	46.1 5

Operator Name: CIMAREX ENERGY COMPANY Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H **Casing Attachments** String Type: SURFACE Casing ID: 1 **Inspection Document: Spec Document: Tapered String Spec:** Casing Design Assumptions and Worksheet(s): Triste_Draw_25_Fed_Com_14H_Casing_Assumptions_03-31-2017.pdf Casing ID: 2 String Type: INTERMEDIATE Inspection Document: **Spec Document: Tapered String Spec:** Casing Design Assumptions and Worksheet(s): Triste Draw 25 Fed Com 14H Casing Assumptions 03-31-2017.pdf Casing ID: 3 String Type: PRODUCTION **Inspection Document: Spec Document:**

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Triste_Draw_25_Fed_Com_14H_Casing_Assumptions_03-31-2017.pdf

Page 3 of 6

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Number: 14H

Casing Attachments

Casing ID: 4

String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Triste_Draw_25_Fed_Com_14H_Casing_Assumptions_03-31-2017.pdf

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1270	616	1.72	13.5	1058	50	Class C	Bentonite
SURFACE	Tail		0	1270	165	1.34	14.8	220	25	Class C	LCM
INTERMEDIATE	Lead		0	5010	940	1.88	12.9	1766	50	35:65 (Poz:C)	Salt, Bentonite
INTERMEDIATE	Tail		0	5010	292	1.34	14.8	391	25	Class C	LCM
PRODUCTION	Lead		0	8944	210	6.18	9.2	1295	25	Class C	Extender, Salt, Strength Enhancement, LCM, Fluid loss, Retarder
PRODUCTION	Tail		Ö	8944	1016	1.3	14.2	1320	10	50:50 (Poz:H)	Salt, Bentonite, Fluid loss, Dispersant, SMS
PRODUCTION	Lead		8944	1369	210	6.18	9.2	1295	25	Class C	Extender, Salt, Strength Enhancement, LCM, Fluid Loss, Retarder
PRODUCTION	Tail		8944	1369 2	1016	1.3	14.2	1320	10	50:50 (Poz:H)	Salt, Bentonite, Fluid Loss, Dispersant, SMS

Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials will be kept on location at all times in order to combat lost circulation or unexpected kicks. In order to run DSTs, open hole logs, and casing, the viscosity and water loss may have to be adjusted in order to meet these needs. **Describe the mud monitoring system utilized:** PVT/Pason/Visual Monitoring

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	ЬН	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
5010	1369	OTHER : FW/Cut Brine	8.7	9.2							9
0	1270	SPUD MUD	8.3	8.8							
1270	5010	SALT SATURATED	9.7	10.2							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

No DST Planned

List of open and cased hole logs run in the well:

CNL, DS, GR

Coring operation description for the well:

n/a

Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 4520

Anticipated Surface Pressure: 2441

Anticipated Bottom Hole Temperature(F): 165

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Triste_Draw_25_Fed_Com_14H_H2S_Plan_03-31-2017.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Triste_Draw_25_Fed_Com_14H_Directional_Prelim_03-31-2017.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

Triste Draw 25 Fed Com 14H Drilling Plan 03-31-2017.pdf

Other Variance attachment:

Triste_Draw_25_Fed_Com_14H_Flex_Hose_03-31-2017.pdf

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

PWD disturbance (acres):

Section 3 - Unlined Pits

PWD surface owner:

Injection well mineral owner:

Injection PWD discharge volume (bbl/day):

Would you like to utilize Unlined Pit PWD options? NO Produced Water Disposal (PWD) Location: PWD surface owner: PWD disturbance (acres): Unlined pit PWD on or off channel: Unlined pit PWD discharge volume (bbl/day): Unlined pit specifications: Precipitated solids disposal: Decribe precipitated solids disposal: Precipitated solids disposal permit: Unlined pit precipitated solids disposal schedule: Unlined pit precipitated solids disposal schedule attachment: Unlined pit reclamation description: Unlined pit reclamation attachment: Unlined pit Monitor description: **Unlined pit Monitor attachment:** Do you propose to put the produced water to beneficial use? Beneficial use user confirmation: Estimated depth of the shallowest aquifer (feet): Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected? TDS lab results: Geologic and hydrologic evidence: State authorization: **Unlined Produced Water Pit Estimated percolation:** Unlined pit: do you have a reclamation bond for the pit? Is the reclamation bond a rider under the BLM bond? Unlined pit bond number: Unlined pit bond amount: Additional bond information attachment: Section 4 - Injection Would you like to utilize Injection PWD options? NO Produced Water Disposal (PWD) Location:

PWD disturbance (acres):

Injection well type:	
Injection well number:	Injection well name:
Assigned injection well API number?	Injection well API number:
Injection well new surface disturbance (acres):	
Minerals protection information:	
Mineral protection attachment:	
Underground Injection Control (UIC) Permit?	
UIC Permit attachment:	
Section 5 - Surface Discharge	
Would you like to utilize Surface Discharge PWD options? NO	
Troute you me to dimize our age 2 too large 1 to 5 options. No	
Produced Water Disposal (PWD) Location:	
PWD surface owner:	PWD disturbance (acres):
Surface discharge PWD discharge volume (bbl/day):	
Surface Discharge NPDES Permit?	
Surface Discharge NPDES Permit attachment:	
Surface Discharge site facilities information:	
Surface discharge site facilities map:	
Section 6 - Other	
Would you like to utilize Other PWD options? NO	
Produced Water Disposal (PWD) Location:	
PWD surface owner:	PWD disturbance (acres):
Other PWD discharge volume (bbl/day):	
Other PWD type description:	
Other PWD type attachment:	
Have other regulatory requirements been met?	
Other regulatory requirements attachment:	

Bond Information

Federal/Indian APD: FED

BLM Bond number: NMB001188

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment:



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

SUPO Data Report

09/05/2017

APD ID: 10400012840

Operator Name: CIMAREX ENERGY COMPANY

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Type: OIL WELL

Submission Date: 03/31/2017

reflects

Well Number: 14H

Well Work Type: Drill

Highlighted data reflects the most recent changes

Show Final Text

Section 1 - Existing Roads

Will existing roads be used? NO

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

Triste_Draw_25_Fed_Com_14H_Road_ROW_03-31-2017.pdf

New road type: COLLECTOR

Length: 20

Feet

Width (ft.): 30

Max slope (%): 2

Max grade (%): 6

Army Corp of Engineers (ACOE) permit required? NO

ACOE Permit Number(s):

New road travel width: 15

New road access erosion control: The side slopes of any drainage channels or swales that are crossed will be recontoured to original grade and compacted and mulched as necessary to avoid erosion. Where steeper slopes cannot be avoided, water bars or silt fence will be constructed, mulch/rip-rap applied, or other measures employed as necessary to control erosion. Hay bales, straw waddles or silt fence may also be installed to control erosion as needed. All disturbed areas will be seeded with a mix appropriate for the area unless specified otherwise by the landowner.

New road access plan or profile prepared? NO

New road access plan attachment:

Access road engineering design? NO

Access road engineering design attachment:

Access surfacing type: GRAVEL

Access topsoil source: ONSITE

Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H

Access surfacing type description:

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: Push off and stockpile alongside the location.

Access other construction information: The operator will prevent and abate fugitive dust as needed, whether created by vehicular traffic, equipment operations or other events.

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: CULVERT, LOW WATER

Drainage Control comments: To control and prevent potentially contaminated precipitation from leaving the pad site, a perimeter berm and settlement pond will be installed. Contaminated water will be removed from pond, stored in waste tanks, and disposed of at a state approved facility. Standing water or puddles will not be allowed. Drainage ditches would be established and maintained on the pad and along access roads to divert water away from operations. Natural drainage areas disturbed during construction would be re-contoured to near original condition prior to construction. Erosion Control Best Management Practices would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be obliterated, re-contoured to near original condition prior to construction. Erosion Control Best Management Practices would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be obliterated, re-contoured, and reclaimed to near original condition to re-establish natural drainage.

Road Drainage Control Structures (DCS) description: n/a

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

Triste_Draw_25_Fed_Com_14H_One_Mile_raduis_Existing_wells_03-31-2017.pdf

Existing Wells description:

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Estimated Production Facilities description:

Production Facilities description:

Production Facilities map:

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Number: 14H

Triste Draw 25 CTB West Battery Pad layout and public access 03-31-2017.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

Water source use type: INTERMEDIATE/PRODUCTION CASING,

Water source type: MUNICIPAL

SURFACE CASING Describe type:

Source latitude:

Source longitude:

Source datum:

Water source permit type: WATER RIGHT

Permit Number:

Source land ownership: STATE

Water source transport method: PIPELINE, TRUCKING

Source transportation land ownership: STATE

Water source volume (barrels): 5000

Source volume (acre-feet): 0.6444655

Source volume (gal): 210000

Water source and transportation map:

Triste_Draw_25_Fed_Com_14H_Drlg_Water_Route_03-31-2017.pdf

Water source comments:

New water well? NO

New Water Well Info

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Construction Materials description: The drilling and testing operations will be conducted on a watered and compacted native soil grade. Soft spots will be covered with scoria, free of large rocks (3" diameter). Upon completion as a commercial producer the location will be covered with scoria, free of large rocks (3" dia.) from an existing privately owned gravel pit. In the event no caliche is found onsite, caliche will be hauled in from BLM approved Caliche pit in Sec. 18-23S-33E or Sec 7-24S-34E.

Construction Materials source location attachment:

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Drilling Fluids, drill cuttings, water and other waste produced from the well during drilling

operations.

Amount of waste: 15000 barrels

Waste disposal frequency: Weekly Safe containment description: n/a

Safe containment attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Haul to R360 commercial Disposal

Waste type: GARBAGE

Waste content description: Garbage and trash produced during drilling and completion operations

Amount of waste: 32500 pounds

Waste disposal frequency: Weekly Safe containment description: n/a

Safe containment attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Windmill Spraying Service hauls trash to Lea County Landfill

Reserve Pit

Reserve Pit being used? NO

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Number: 14H

Temporary disposal of produced water into reserve pit?

Reserve pit length (ft.)

Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? NO

Description of cuttings location

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: NO

Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

Triste_Draw_25_Fed_Com_14H_Wellsite_Layout_03-31-2017.pdf

Comments:

Well Name: TRISTE DRAW 25 FEDERAL COM Well Number: 14H

Section 10 - Plans for Surface Reclamation

Type of disturbance: NEW Recontouring attachment:

Drainage/Erosion control construction: To control and prevent potentially contaminated precipitation from leaving the pad site, a perimeter berm and settlement pond will be installed. Contaminated water will be removed from pond, stored in waste tanks, and disposed of at a state approved facility. Standing water or puddles will not be allowed. Drainage ditches would be established and maintained on the pad and along access roads to divert water away from operations. Natural drainage areas disturbed during construction would be re-contoured to near original condition prior to construction. Erosion Control Best Management Practices would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be obliterated, re-contoured, and reclaimed to near original condition to re-establish natural drainage.

Drainage/Erosion control reclamation: All disturbed and re-contoured areas would be reseeded according to specifications. Approved seed mixtures would be certified weed free and consist of grasses, forbs, or shrubs similar to the surrounding area. Compacted soil areas may need to be obliterated and reclaimed to near natural conditions by re-contouring all slopes to facilitate and re-establish natural drainage.

Wellpad long term disturbance (acres): 6.902

Wellpad short term disturbance (acres): 6.902

Access road long term disturbance (acres): 1.162

Access road short term disturbance (acres): 1.162

Pipeline long term disturbance (acres): 26.524794

Pipeline short term disturbance (acres): 3.2969697

Other long term disturbance (acres): 6.075

Other short term disturbance (acres): 0

Total long term disturbance: 40.66379

Total short term disturbance: 11.36097

Reconstruction method: After well plugging, all disturbed areas would be returned to the original contour or a contour that blends with the surrounding landform including roads unless the surface owner requests that they be left intact. In consultation with the surface owners it will be determined if any gravel or similar materials used to reinforce an area are to be removed, buried, or left in place during final reclamation. Salvaged topsoil, if any, would be re-spread evenly over the surfaces to be re-vegetated. As necessary, the soil surface would be prepared to provide a seedbed for re-establishment of desirable vegetation. Site preparation may include gouging, scarifying, dozer track-walking, mulching, or fertilizing. Reclamation, Re-vegetation, and Drainage: All disturbed and re-contoured areas would be reseeded using techniques outlined under Phase I and II of this plan or as specified by the land owner. Approved seed mixtures would be certified weed free and consist of grasses, forbs, or shrubs similar to the surrounding area. Compacted soil areas may need to be obliterated and reclaimed to near natural conditions by re-contouring all slopes to facilitate and re-establish natural drainage. Topsoil redistribution: Salvaged topsoil, if any, would be re-spread evenly over the surfaces to be re-vegetated.

Soil treatment: As necessary, the soil surface would be prepared to provide a seedbed for re-establishment of desirable vegetation. Site preparation may include gouging, scarifying, dozer track-walking, mulching or fertilizing. **Existing Vegetation at the well pad:**

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road:

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline:

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances:

Existing Vegetation Community at other disturbances attachment:

Non native seed used? NO	
Non native seed description:	
Seedling transplant description:	
Will seedlings be transplanted for this project? NO	
Seedling transplant description attachment:	
Will seed be harvested for use in site reclamation?	NO
Seed harvest description:	
Seed harvest description attachment:	
Seed Management	
Seed Table	
Seed type:	Seed source:
Seed name:	
Source name:	Source address:
Source phone:	
Seed cultivar:	
Seed use location:	
PLS pounds per acre:	Proposed seeding season:
Seed Summary	Total pounds/Acre:
Seed Type Pounds/Acre	
Seed reclamation attachment:	
Operator Contact/Responsible Offici	al Contact Info
First Name:	Last Name:
Phone:	Email:
Seedbed prep:	
Seed BMP:	

Well Number: 14H

Operator Name: CIMAREX ENERGY COMPANY
Well Name: TRISTE DRAW 25 FEDERAL COM

Seed method:

Existing invasive species? NO

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Number: 14H

Weed treatment plan description: n/a

Weed treatment plan attachment:

Monitoring plan description: n/a

Monitoring plan attachment:

Success standards: n/a

Pit closure description: n/a

Pit closure attachment:

Section 11 - Surface Ownership

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Section 12 - Other Information

Right of Way needed? YES

Use APD as ROW? YES

ROW Type(s): 281001 ROW - ROADS,288100 ROW - O&G Pipeline,288101 ROW - O&G Facility Sites,288103 ROW - Salt Water Disposal Pipeline/Facility,289001 ROW- O&G Well Pad,FLPMA (Powerline),Other

ROW Applications

Well Name: TRISTE DRAW 25 FEDERAL COM

Well Number: 14H

SUPO Additional Information:

Use a previously conducted onsite? YES

Previous Onsite information: Onsite with BLM (Jeff Robertson) & Cimarex (Barry Hunt) on Feb 21, 2017. V-Door East. Top soil East. Interim reclamation: All sides. Access road at NW corner, west into access road to the battery.

Other SUPO Attachment

Triste_Draw_25_CTB_West_Access_Road_03-31-2017.pdf

Triste_Draw_25_CTB_West_Powerline_ROW_03-31-2017.pdf

Triste_Draw_25_CTB_West_Gas_Sales_ROW_03-31-2017.pdf

Triste_Draw_25_CTB_West_SWD_ROW_03-31-2017.pdf

Triste_Draw_25_Fed_Com_14H_Flow_line_ROW_03-31-2017.pdf

Triste_Draw_25_Fed_Com_14H_Gas_Lift_ROW_03-31-2017.pdf

Triste_Draw_25_Fed_Com_14H_Public_Access_03-31-2017.pdf

Triste_Draw_25_Fed_Com_14H_SUPO_03-31-2017.pdf

Triste_Draw_25_Fed_Com_14H_Road_Description_03-31-2017.pdf

Triste_Draw_25_Fed_Com_14H_Temp_Frac_Water_Route_03-31-2017.pdf

Triste_Draw_25_Fed_Com_14H_Gas_Capture_Plan_08-07-2017.pdf

Triste_Draw_25_Fed_Com_14H_Interim_Reclamation_08-07-2017.pdf