

Submit 1 Copy To Appropriate District  
Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

HOBBS OCD  
OCT 17 2017  
RECEIVED

WELL API NO. 30-025-24968	
5. Indicate Type of Lease STATE FEE X	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name H. T. MATTERN NCT-B	
8. Well Number 19	
9. OGRID Number 4323	
10. Pool name or Wildcat BLINEBERRY	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,498' GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INT

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

INT TO PA  
P&A NR Pm.  
P&A R

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A X  
CASING/CEMENT JOB ☐  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/01/17 MI & RU, NDWH, POOH W/ RODS & BHA, RU BOP'S, POOH W/ TBG.

10/02/17 RIH & TAG CIBP @ 6,092', MIX & SPOT 25 SX CL "C" CMT FROM 6,092' - 5,846'. M. WHITAKER OK PLUG.

10/03/17 RIH & TAG @ 5,800', RIH W/ CIBP & SET @ 5,450', TEST CSG 500# GOOD, MIX & SPOT 25 SX CL "C" CMT FROM 5,450' - 5,250'.

10/04/17 TEST PLUG 600# GOOD, RIH & TAG @ 5,212', MIX & SPOT 25 SX CL "C" CMT FROM 5,180' - 4,930', MIX & SPOT 85 SX CL "C" CMT FROM 4,015' - 3,225', MIX & SPOT 50 SX CL "C" CMT FROM 2,950' - 2,450'.

10/05/17 RIH TAG @ 2,419', PERF @ 1,254', MIX & CIR 60 SX CL "C" CMT FROM 1,254' - 1,154', WOC & TAG @ 1,003' PERF @ 400'.

10/06/17 MIX & CIR 120 SX CL "C" CEMENT FROM 400' BACK TO SURFACE ON BOTH STRINGS. RD & MOVE OUT, CLEAN LOCATION. TURN OVER TO RECLAMATION.

ALL CEMENT PLUGS CLASS "C", W/ CLOSED LOOP SYSTEM USED.  
CA BOND 0329

Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.  
Restoration Due By 10-05-2018

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Type or print name Monty L. McCarver E-mail address: monty.mccarver@cjes.com PHONE: 713-325-6288

For State Use Only

APPROVED BY:

Conditions of Approval (if any):

TITLE P.E.S.

DATE 10/18/2017