District I 1625 N. French Dr., Hobbs, NM 8900 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Azlee, NM 910 District IV 1220 S. St. Francis Dr., Santa Fe, N97505 Santa Fe, NM 87505		nit Original Appropriate trict Office
GAS CAPTURE PLAN		
Date: <u>11/20/2017</u> X Original Operator & OGRID No.: Matador Production Company	(22893	7)
Amended - Reason for Amendment:	<u> </u>	

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well	API	SHL (ULSTR)	SHL Footages	Expected MCF/D	Flared or Vented	Comments
Nina Cortell Fed Com 122H	30-025-	M-3-22S-32E	150 FSL & 1906 FWL	2500	28 days	Flare 28 days on FB before turn into TB
Nina Cortell Fed Com 132H	30-025-	M-3-22S-32E	150 FSL & 1847 FWL	2500	28 days	Flare 28 days on FB before turn into TB
Nina Cortell Fed Com 202H	30-025- 44 5 43	M-3-22S-32E	150 FSL & 1876 FWL	2500	28 days	Flare 28 days on FB before turn into TB

Gathering System and Pipeline Notification

The well will be connected to a production facility after flowback operations are complete so long as the gas transporter system is in place. The gas produced from the production facility should be connected to an as yet to be designated gas gathering systems located in Lea County, NM. It will require an unknown length of pipeline to connect the facility to a gathering system. Matador Production Company periodically provides a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future to different gathering companies. If changes occur that will affect the drilling and completion schedule, Matador Production Company will notify the gathering companies if the gas produced from the well will be processed at a processing plant further downstream and, although unanticipated, any issues with downstream facilities could cause flaring at the wellhead. The actual flow of the gas will be based on compression operating parameters and gathering system pressures measured when the well starts producing.

Flowback Strategy

After fracture treatment/completion operations (flowback), the well will be produced to temporary production tanks and the gas will be flared or vented. During flowback, the fluids and sand content will be monitored. If the produced fluids contain minimal sand, then the well will be turned to production facilities. The gas sales should start as soon as the well starts flowing through the production facilities, unless there are operational issues on the midstream system at that time. Based on current information, it is Matador's belief the system will be able to take the gas upon completion of the well.

Safety requirements during cleanout operations may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint, but determined to be impractical, to reduce the amount of gas flared.

- Power Generation On lease
 - o Operating a generator will only utilize a portion of the produced gas and the remainder of gas would still need to be flared.
 - o Power generation also requires an agreement with a power company that is willing to purchase the gas. The terms of any such agreement typically require a long-term commitment from the operator at certain and steady deliverables. With gas decline rates and the unpredictability of markets, it is impracticable for the operator to agree to a long-term commitment because as the wells decline the operator would be burdened with penalties for failure to meet the deliverables.
- Compressed Natural Gas On lease