Submit 1 Copy To Appropriate District State of Ne	
<u>District 1</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 Energy, Minerals and	
$\frac{\text{District II}}{\text{District II}} - (575) 748-1283$	3002544957
811 S. First St., Artesia, NM 88210         OIL CONSERVA           District III - (505) 334-6178         1220 South St	Enomotic Dr. S. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	STATE     STATE     FEE       IM \$7509     6 2018     6. State Oil & Gas Lease No.
<u>District IV</u> – (505) 476-3460 Salila Fe, F 1220 S. St. Francis Dr., Santa Fe, NM	o. State Off & Gas Lease No.
87505 SUNDRY NOTICES AND REPORTS ON W	RECEIVED
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C	-101) FOR SUCH MAMBA 30 STATE COM
PROPOSALS.)         1. Type of Well: Oil Well X         Gas Well         Other	8. Well Number 704
2. Name of Operator	9. OGRID Number
EOG RESOURCES	7377
3. Address of Operator	10. Pool name or Wildcat
P O BOX 2267, MIDLAND TX 797 4. Well Location	702 98092-UPPER WOLFCAMP
Unit Letter O : 363 feet from the SOUTH line and 1509 feet from the EAST line	
Section 30 Township - Pange - NMPM County	
11. Elevation (Show wheth	er DR. RKB. RT. GR. etc.)
GL 353	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	
TEMPORARILY ABANDON CHANGE PLANS	
PULL OR ALTER CASING	CASING/CEMENT JOB
CLOSED-LOOP SYSTEM	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	
proposed completion or recompletion.	
09/15/18 8-3/4" HOLE 09/18/18 RUN 7-5/8", 29.7#, ECP-110, BTC SCC (0' - 931')	
RUN 7-5/8", 29.7#, HCP-110, FXL (931' - 11,913') Lead Cement w/ 285 sx Class A (14.9 ppg, 3.53 yld), Tail w/115 sx Class A (15.6 ppg, 1.23 yld)	
Test casing to 2,600 psi for 30 min - Good. Circ 70 sx cement to surface	
Resume drilling	
Spud Date: 07/22/18 Rig Rele	ase Date:
	the bast of my lynamiader and halisf
I hereby certify that the information above is true and complete to	the best of my knowledge and belief.
SIGNATURE TITLE	Sr. Regulatory Administrator DATE
	u amily fallia@aagraaauraaa.amaxm 422.949.0462
For State Use Only	ddress: emily_follis@eogresources.comONE: 432-848-9163
For State Use Only	
For State Use Only APPROVED BY:	Petroleum Engineer