

Submit 1 Copy To Appropriate
Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88241

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87401

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

State of New Mexico

Energy, Minerals and Natural Resources

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

Revised July 18, 2013

WELL API NO.

30-025-45696

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

320555

7. Lease Name or Unit Agreement Name

PYTHON 36 STATE COM

8. Well Number

#703H

9. OGRID Number

7377

10. Pool name or Wildcat

[98180] WC-025 G-09 S253309P; UPR WOLFCAMP

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

EOG RESOURCES

3. Address of Operator

P O BOX 2267, MIDLAND TX 79702

4. Well Location

Unit Letter N : 546 feet from the SOUTH line and 1716 feet from the WEST line
Section 36 Township 24S Range 32E NMPM County LEA COUNTY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3559' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: DRILL CSG ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of
proposed completion or recompletion.

05/07/19 12-1/4" HOLE

05/07/19 Surface Casing @ 1,130'

Ran 9-5/8" 40# J-55 LTC

Cement w/ 370 sx Class C (1.76 yld, 13.5 ppg), Tail w/90 sx Class C (1.36 yld, 14.8 ppg)

Test casing to 1,500 psi for 30 min - OK. Circ 160 sx cement to surface Resume drilling 8-3/4" hole

Spud Date:

05/07/19

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Sr. Regulatory Administrator

DATE 05/20/19

Type or print name Emily Follis

E-mail address: emily_follis@eogresources.com PHONE: 432-848-9163

For State Use Only

APPROVED BY:

TITLE

DATE

Conditions of Approval (if any):