Submit 1 Copy To Appropriate District	State of New Mexico	Form C-103
Office <u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240	/ ,	WELL API NO.
<u>District II</u> (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-025-45855 5. Indicate Type of Lease
District III - (505) 334-6178	1220 South St. France Dr.	STATE STATE
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460	1220 South St. Francis Dr. Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	A. 20, CO	325384
SUNDRY NOTICES AND REPORTS ON TALLS 7. Lease Name or Unit Agreement Name		
(DO NOT USE THIS FORM FOR PROP	OSALS TO DRILL OR TO DEEPEN OCTUG BACK TO A JCATION FOR PERMIT" (FORM C-101) HOT NICH	
PROPOSALS.)	ICATION FOR PERMIT (FORM C-101) IS SUCH	DURANGO 2 STATE
1. Type of Well: Oil Well	Gas Well 📋 Other	8. Well Number #701H
2. Name of Operator EOG RE	SOURCES	9. OGRID Number 7377
3. Address of Operator		10. Pool name or Wildcat
	X 2267, MIDLAND TX 79702	[98092] WC-025 G-09 S243336I; UPPER WOLFC
4. Well Location Unit Letter D 258 feet from the NORTH line and 299 feet from the WEST line		
Section 2	Township 25S Range 33E	NMPM County LEA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3478 GL		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
		BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A		
PULL OR ALTER CASING		
CLOSED-LOOP SYSTEM		
OTHER:		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
05/17/19 8-3/4" hole	completion.	
05/17/19 Intermediate Casing @ 11,782' Ran 7-5/8", 29.7#, ECP-110 BTC SCC (0' - 1,010')		
Ran 7-5/8", 29.7#, HCP-110 MO-FXL (1,010'- 11,782') Stage 1: Lead Cement w/ 480 sx Class C (1.04 yld, 14.0 ppg)		
Test casing to 2 600 psi for 30 min - Good. Did not circ cement to surface. TOC @ 7,000' by Calc		
Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.5 yld, 14.8 ppg) TOC @ 6,195 by Calc Stage 3: Top out w/ 164 sx Class C (1.37 yld, 14.8 ppg) TOC @ surface Resume Drilling 6-3/4" hole		
•		
Spud Date: 05/11/19	Rig Release Date:	
Lhereby certify that the information	above is true and complete to the best of my knowled	ice and helief
SIGNATURE M TITLE Sr. Regulatory Administrator DATE 05/21/19		
Type or print name Emily Follis E-mail address: emily_follis@eogresources.comONE: 432-848-9163		
renoted in Engineer		
APPROVED BY:	TITLE	DATEOO [2011]
ے :(f any):		