Office		tate of New Me			Form C-103
District I – (575) 393-6161	Energy, M	inerals and Natu	ral Resources	WELL API N	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	OIL CO	ICEDI/A TION	DIVICION	WELL AFTY	0-025-46442
OIL CONSERVATION DIVISION  District III – (505) 334-6178  OIL CONSERVATION DIVISION  1220 South St. Francis Dr.			5. Indicate T	ype of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410			STATI		
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	3	ania re, Nivi o	303	6. State Oil &	c Gas Lease No.
87505					325728
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A				7. Lease Nam	ne or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			ADDER 31 STATE		
1. Type of Well: Oil Well 🔀 Gas Well 🗌 Other			8. Well Number #706H		
Name of Operator     EOG RESOURCES			9. OGRID Number 7377		
3. Address of Operator			10. Pool name or Wildcat		
P O BOX 2267, MIDLAND TX 79702			98180 WC-02	5 G-09 S253309P; UPR WOLFCAMP	
4. Well Location Unit Letter P	:687 feet fr	om the SOUTH	line and 87	'5 feet	from the EAST line
Section 31			nge 33E	NMPM	County LEA
	11. Elevation (S	Show whether DR,	RKB, RT, GR, etc	.)	
<u> </u>		3505 GL			
12. Check	Appropriate Bo	x to Indicate N	ature of Notice,	, Report or Otl	ner Data
NOTICE OF	INTENTION TO	):	SUE	SEQUENT I	REPORT OF:
PERFORM REMEDIAL WORK			REMEDIAL WOR		
	CHANGE PLAN		COMMENCE DR	_	
-	MULTIPLE CON	MPL 🗆	CASING/CEMEN	IT JOB	
DOWNHOLE COMMINGLE [CLOSED-LOOP SYSTEM [	_ ]				
OTHER:				LL CSG	<u> </u>
12 Describe proposed or con	nnleted operations	(Clearly state all r	ertinent details an	d give portinent	dates, including estimated date
of starting any proposed	work). SEE RULE				
of starting any proposed of proposed completion or r 12/06/19 8-3/4" HOLE	work). SEE RULE completion.				
of starting any proposed of proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N	work). SEE RULE completion.				
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0	work). SEE RULE ecompletion.  ID, 11,760' TVD ' - 1,007')				
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' MC asing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class	work). SEE RULE ecompletion.  ID, 11,760' TVD  ' - 1,007') .007' - 11,809') H (1.20 yld, 15.6 ppg)	19.15.7.14 NMAC	. For Multiple Co	ompletions: Attac	ch wellbore diagram of
of starting any proposed of proposed completion or responsed completion or response to the start of the start	work). SEE RULE ecompletion. ID, 11,760' TVD '-1,007') ,007'-11,809') H (1.20 yld, 15.6 ppg) od Did not circ cement sx Class C (1.50 yld, 1	19.15.7.14 NMAC	. For Multiple Co	ompletions: Attac	
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' M Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class Fest casing to 2,500 psi for 30 min - Gostage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3	work). SEE RULE ecompletion. ID, 11,760' TVD '-1,007') ,007'-11,809') H (1.20 yld, 15.6 ppg) od Did not circ cement sx Class C (1.50 yld, 1	19.15.7.14 NMAC	. For Multiple Co	ompletions: Attac	ch wellbore diagram of
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' MC asing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ECP-110 MC-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007') ,007'-11,809') +1 (1.20 yld, 15.6 ppg) od Did not circ cement sx Class C (1.50 yld, 17 yld, 14.8 ppg) TOC @	19.15.7.14 NMAC	. For Multiple Co	ompletions: Attac	HOBBS OCD
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I cest casing to 2,500 psi for 30 min - Gos Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007') ,007'-11,809') H (1.20 yld, 15.6 ppg) old Did not circ cement sx Class C (1.50 yld, 17 yld, 14.8 ppg) TOC @	19.15.7.14 NMAC	. For Multiple Co	ompletions: Attac	HOBBS OCD
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I Test casing to 2,500 psi for 30 min - Gostage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' MD Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMag	work). SEE RULE ecompletion.  ID, 11,760' TVD  ' - 1,007') .007' - 11,809') - (1,20 yld, 15.6 ppg) od Did not circ cement sx Class C (1.50 yld, 1 7 yld, 14.8 ppg) TOC @  0, 12,426' TVD D06' and 16,989') g-H + 0.25% CPT-30 +	19.15.7.14 NMAC to surface, TOC @ 7 4.8 ppg) surface	For Multiple Co ,300' by Calc	empletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMagaump plug, no casing test (Wet shoe). Evailing on CBL RR	work). SEE RULE ecompletion.  ID, 11,760' TVD  ' - 1,007') .007' - 11,809') - (1,20 yld, 15.6 ppg) od Did not circ cement sx Class C (1.50 yld, 1 7 yld, 14.8 ppg) TOC @  0, 12,426' TVD D06' and 16,989') g-H + 0.25% CPT-30 +	19.15.7.14 NMAC to surface, TOC @ 7 4.8 ppg) surface	For Multiple Co ,300' by Calc	empletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class   Fest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV	work). SEE RULE ecompletion.  ID, 11,760' TVD  ' - 1,007') .007' - 11,809') - (1,20 yld, 15.6 ppg) od Did not circ cement sx Class C (1.50 yld, 1 7 yld, 14.8 ppg) TOC @  0, 12,426' TVD D06' and 16,989') g-H + 0.25% CPT-30 +	19.15.7.14 NMAC to surface, TOC @ 7 4.8 ppg) surface	For Multiple Co ,300' by Calc	empletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMagaump plug, no casing test (Wet shoe). Evailing on CBL RR	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC 6  1, 12,426' TVD  10  10  10  10  11  11  11  12  12  13  14  15  16  16  17  17  18  18  18  18  18  18  18  18	19.15.7.14 NMAC to surface, TOC @ 7 4.8 ppg) surface	. For Multiple Co ,300' by Calc KT-C + 0.45% CPT-2 29' by Calc	empletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Gor Stage 2: Bradenhead squeeze w/ 1,00 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMadump plug, no casing test (Wet shoe). Evaiting on CBL RR Completion to follow	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC 6  1, 12,426' TVD  10  10  10  10  11  11  11  12  12  13  14  15  16  16  17  17  18  18  18  18  18  18  18  18	19.15.7.14 NMAC to surface, TOC @ 7 4.8 ppg) g surface 0.4% D-3 + 0.1% G urface, TOC @ 10.83	7. For Multiple Co 1,300' by Calc 1,300' by Calc 1,300' by Calc	empletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Gor Stage 2: Bradenhead squeeze w/ 1,00 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMadump plug, no casing test (Wet shoe). Evaiting on CBL RR Completion to follow	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC 6  1, 12,426' TVD  10  10  10  10  11  11  11  12  12  13  14  15  16  16  17  17  18  18  18  18  18  18  18  18	19.15.7.14 NMAC to surface, TOC @ 7 4.8 ppg) g surface 0.4% D-3 + 0.1% G urface, TOC @ 10.83	. For Multiple Co ,300' by Calc KT-C + 0.45% CPT-2 29' by Calc	empletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' N Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Gor Stage 2: Bradenhead squeeze w/ 1,00 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMadump plug, no casing test (Wet shoe). Evaiting on CBL RR Completion to follow	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC (6  1, 12,426' TVD  10  10  10  10  11  11  12  12  14  15  16  16  17  17  18  18  18  18  18  18  18  18	to surface, TOC @ 7 4.8 ppg) g surface 0.4% D-3 + 0.1% G urface, TOC @ 10,85	7. For Multiple Co 7.300' by Calc 6.300' by Calc 6.29' by Calc 6.29' by Calc	ompletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' M Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMagaump plug, no casing test (Wet shoe). Evailing on CBL RR Completion to follow  Spud Date: 11/14/19	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC (6  1, 12,426' TVD  10  10  10  10  11  11  12  12  14  15  16  16  17  17  18  18  18  18  18  18  18  18	to surface, TOC @ 7 4.8 ppg) g surface 0.4% D-3 + 0.1% G urface, TOC @ 10,85	7. For Multiple Co 7.300' by Calc 6.300' by Calc 6.29' by Calc 6.29' by Calc	ompletions: Attac	HOBBS OCD DEC 3 0 2019 RECEIVED
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' M Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I cest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 C2mmcht w/ 580 sx Class H + 1% PreMadump plug, no casing test (Wet shoe). Example on CBL RR Completion to follow  Spud Date: 11/14/19	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC (6  1, 12,426' TVD  10  10  10  10  11  11  12  12  14  15  16  16  17  17  18  18  18  18  18  18  18  18	to surface, TOC @ 7 4.8 ppg) g surface  0.4% D-3 + 0.1% G urface, TOC @ 10,85  Rig Release Da	T-C + 0.45% CPT-29 by Calc  12/13/19  st of my knowledge	empletions: Attack	HOBBS OCD  DEC 3 0 2019  RECEIVED  Pg)
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' M Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Charlet w/ 580 sx Class H + 1% PreMad Sump plug, no casing test (Wet shoe). Example on CBL RR Completion to follow  Spud Date: 11/14/19  I hereby certify that the information of the completion of the casing test (Wet shoe). If the completion of the casing test (Wet shoe). If the completion of the casing test (Wet shoe). If the casing	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC (6  1, 12,426' TVD  10  10  10  10  11  11  12  12  14  15  16  16  17  17  18  18  18  18  18  18  18  18	to surface, TOC @ 7 4.8 ppg) g surface  0.4% D-3 + 0.1% G urface, TOC @ 10,8;  Rig Release Da  complete to the be	The Multiple Constitution of the Constitution	empletions: Attack	HOBBS OCD DEC 3 0 2019 RECEIVED Pg) DATE 12/19/19
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832" M Casing shoe @ 11,809" MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class Fest casing to 2,500 psi for 30 min - Gostage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 Froduction Hole @ 17,479' MD (2asing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMagump plug, no casing test (Wet shoe). Dividing on CBL RR Completion to follow  Spud Date:  Type or print name Emily Follist  Type or print name Emily Follist	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC (6  1, 12,426' TVD  10  10  10  10  11  11  12  12  14  15  16  16  17  17  18  18  18  18  18  18  18  18	to surface, TOC @ 7 4.8 ppg) g surface  0.4% D-3 + 0.1% G urface, TOC @ 10,8;  Rig Release Da  complete to the be	The Multiple Constitution of the Constitution	empletions: Attack	HOBBS OCD  DEC 3 0 2019  RECEIVED  Pg)
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832' M Casing shoe @ 11,809' MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class I fest casing to 2,500 psi for 30 min - Got Stage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 6-3/4 Hole 12/03/19 Production Hole @ 17,479' ME Casing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Charlet w/ 580 sx Class H + 1% PreMad Sump plug, no casing test (Wet shoe). Example on CBL RR Completion to follow  Spud Date: 11/14/19  I hereby certify that the information of the completion of the casing test (Wet shoe). If the completion of the casing test (Wet shoe). If the completion of the casing test (Wet shoe). If the casing	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC (6  1, 12,426' TVD  10  10  10  10  11  11  12  12  13  14  15  16  16  17  17  18  18  18  18  18  18  18  18	to surface, TOC @ 7 4.8 ppg) g surface  0.4% D-3 + 0.1% G urface, TOC @ 10,83  Rig Release Da  complete to the be E-mail address	For Multiple Co., 300' by Calc  XT-C + 0.45% CPT-2  Te: 12/13/19  st of my knowledge egulatory Admining emily_follis@e	ge and belief.	HOBBS OCD DEC 3 0 2019 RECEIVED Pg) DATE 12/19/19
of starting any proposed proposed completion or r 12/06/19 8-3/4" HOLE 12/06/19 Intermediate Hole @ 11,832" M Casing shoe @ 11,809" MD Ran 7-5/8", 29.7#, ICYP-110 BTC SC (0 Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (1 Stage 1: Lead Cement w/ 390 sx Class Fest casing to 2,500 psi for 30 min - Gostage 2: Bradenhead squeeze w/ 1,000 Stage 3: Top out w/ 123 sx Class C (1.3 12/03/19 Froduction Hole @ 17,479' MD (2asing shoe @ 17,459' MD, 12,426' TV 5-1/2", 20#, ICYP-110, TXP (MJ @ 11,9 Cement w/ 580 sx Class H + 1% PreMagump plug, no casing test (Wet shoe). Dividing on CBL RR Completion to follow  Spud Date:  Type or print name Emily Follist  Type or print name Emily Follist	work). SEE RULE ecompletion.  ID, 11,760' TVD  '-1,007')  007'-11,809')  1 (1.20 yld, 15.6 ppg)  1 (1.20 yld, 15.6 ppg)  2 (1.50 yld, 1  7 yld, 14.8 ppg) TOC (6  1, 12,426' TVD  10  10  10  10  11  11  12  12  13  14  15  16  16  17  17  18  18  18  18  18  18  18  18	to surface, TOC @ 7 4.8 ppg) g surface  0.4% D-3 + 0.1% G urface, TOC @ 10,83  Rig Release Da  complete to the be E-mail address	The Multiple Constitution of the Constitution	ge and belief.	HOBBS OCD DEC 3 0 2019 RECEIVED Pg) DATE 12/19/19