

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 S. St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-46735
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 313956
7. Lease Name or Unit Agreement Name NEPTUNE 10 STATE COM
8. Well Number #205H
9. OGRID Number 7377
10. Pool name or Wildcat 59900 TRIPLE X; BONE SPRING

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-DRILL OR TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
EOG RESOURCES

3. Address of Operator
P O BOX 2267, MIDLAND TX 79702

4. Well Location
Unit Letter **P** : **870** feet from the **SOUTH** line and **964** feet from the **EAST** line
Section **10** Township **24S** Range **33E** NMPM County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
36080 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: **DRILL CSG** ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/07/2020 12-1/4" hole
03/07/2020 1st Intermediate Hole @ 5,185' MD, 5,185' TVD
Casing shoe @ 5,170' MD, 5,123' TVD
Ran 9-5/8", 40#, J-55 LTC (0' - 3,777')
Ran 9-5/8", 40#, HCK-55 LTC (3,777' - 5,170')
Lead Cement w/ 1,086 sx Class C (2.26 yld, 12.7 ppg), Trail w/305 sx Class C (1.39 yld, 14.8 ppg)
Test casing to 2,000 psi for 30 min - good Circ 407 sx cement to surface. Resume drilling 8-3/4" hole

Spud Date:

01/30/2020

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Sr. Regulatory Administrator

DATE 03/10/2020

Type or print name Emily Follis

E-mail address: emily_follis@eogresources.com PHONE: 432-848-9163

For State Use Only

APPROVED BY:

TITLE

L.M.

DATE

5/5/20

Conditions of Approval (if any):