

ATS-08-530

6011
OCD-HOBBS
680

Form 3160-3
(February 2005)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No 1004-0137
Expires March 31, 2007

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM 118720
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator Marbob Energy Corporation		7. If Unit or CA Agreement, Name and No
3a. Address P.O. Box 227, Artesia, NM 88211-0228		8. Lease Name and Well No. <37202> B-52 Federal #2
3b. Phone No. (include area code) 505-748-3303		9. API Well No. 30-025-38969
4. Location of Well (Report location clearly and in accordance with any State requirements*) At surface 330' FNL & 660' FEL At proposed prod zone Capitan Controlled Water Basin Unit A		10. Field and Pool, or Exploratory Lusk; Bone Spring North
14. Distance in miles and direction from nearest town or post office* About 14 miles from Maljamar, NM		11. Sec, T R M or Blk and Survey or Area Section 5, T19S - R32E
15. Distance from proposed* location to nearest property or lease line, ft (Also to nearest drig unit line, if any) 330'	16. No. of acres in lease 360.00	12. County or Parish Lea County
17. Spacing Unit dedicated to this well 40	13. State NM	
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft	19. Proposed Depth 9800'	20. BLM/BIA Bond No. on file NMB000412
21. Elevations (Show whether DF, KDB, RT, GL, etc) 3676' GL	22. Approximate date work will start* 05/04/2008	23. Estimated duration 30 Days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form

- | | |
|--|---|
| 1 Well plat certified by a registered surveyor | 4 Bond to cover the operations unless covered by an existing bond on file (see Item 20 above) |
| 2 A Drilling Plan | 5 Operator certification |
| 3 A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) | 6 Such other site specific information and/or plans as may be required by the BLM. |

25. Signature <i>Nancy T. Agnew</i>	Name (Printed/Typed) Nancy T. Agnew	Date 04/04/2008
Title Land Department		

Approved by (Signature) /s/ Don Peterson	Name (Printed/Typed) /s/ Don Peterson	Date JUN 5 2008
Title FIELD MANAGER		Office CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon
Conditions of approval, if any, are attached.
APPROVAL FOR TWO YEARS

Title 18 USC Section 1001 and Title 43 USC Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

*(Instructions on page 2)

RECEIVED

Kz

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

JUN 10 2008
HOBBS OCD

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS
AND SPECIAL STIPULATIONS
ATTACHED

STATEMENT ACCEPTING RESPONSIBILITY FOR OPERATIONS

The undersigned accepts all applicable terms, conditions, stipulations, and restrictions concerning operations conducted on the leased land or portion thereof, as described below:

Date: April 4, 2008

Lease #: NMNM118700
B-52 Federal #2

Legal Description: Sec. 5-T19S-R32E
Eddy County, New Mexico

Formation(s): Permian

Bond Coverage: Statewide

BLM Bond File #: NMB000412

Marbob Energy Corporation

Nancy Agnew
Nancy Agnew
Land Department

State of New Mexico

DISTRICT I
1625 N. FRENCH DR., HOBBS, NM 88240

Energy, Minerals and Natural Resources Department

Form C-102

DISTRICT II
1301 W. GRAND AVENUE, ARTESIA, NM 88210

OIL CONSERVATION DIVISION
1220 SOUTH ST. FRANCIS DR.
Santa Fe, New Mexico 87505

Revised October 12, 2005
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV
1220 S. ST. FRANCIS DR., SANTA FE, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

AMENDED REPORT

API Number 30-025-38969		Pool Code 41440 41450	Pool Name LUSK; BONE SPRING North
Property Code 37202	Property Name B-52 FEDERAL		Well Number 2
OGRID No. 14049	Operator Name MARBOB ENERGY CORPORATION		Elevation 3676'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	5	19-S	32-E		330	NORTH	660	EAST	LEA

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County				
<table border="1"> <tr> <td>Dedicated Acres 40 ✓</td> <td>Joint or Infill</td> <td>Consolidation Code</td> <td>Order No.</td> </tr> </table>										Dedicated Acres 40 ✓	Joint or Infill	Consolidation Code	Order No.
Dedicated Acres 40 ✓	Joint or Infill	Consolidation Code	Order No.										

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

				<p>OPERATOR CERTIFICATION</p> <p>I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division</p> <p><i>Nancy Agnew</i> 4/1/08 Signature Date</p> <p>Nancy Agnew Printed Name</p>	
<p>DETAIL</p> <p>3676.4' 3678.7'</p> <p>○ 600'</p> <p>3670.5' 3671.2'</p>				<p>GEODETIC COORDINATES NAD 27 NME SURFACE LOCATION</p> <p>Y=617257.2 N X=669754.1 E</p> <p>LAT.=32 695724" N LONG.=103.781527" W</p>	
<p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p>					
<p>Date Surveyed MARCH 11, 2008 LA</p> <p>Signature & Seal of Professional Surveyor</p> <p><i>Ronald J. Eidson</i> 3239</p> <p>08-11-0258</p>					
<p>Certificate No. GARY G. EIDSON 12641 RONALD J. EIDSON 3239</p>					

**MARBOB ENERGY CORPORATION
DRILLING AND OPERATIONS PROGRAM**

**B-52 Federal #2
330' FNL & 660' FEL
Section 5, T19S, R32E
Lea County, New Mexico**

In conjunction with Form 3160-3, Application for Permit to Drill subject well, Marbob Energy Corporation submits the following ten items of pertinent information in accordance with BLM requirements.

1. Geological surface formation: Permian
2. The estimated tops of geologic markers are as follows:

Rustler	1150'	Queen	3806'
TOS	1280'	Delaware	4540'
BOS	2660'	Bone Spring Lime	7070'
Yates	2880'	1 st Sand	8410'
7 Rivers	3330'	2 nd Sand	9140'
		TD	9800'

PERMIT TO DRILL
 APR 23 2008
 BUREAU OF LAND MANAGEMENT
 OFFICE OF THE DISTRICT MANAGER
 ALBUQUERQUE, NEW MEXICO

3. The estimated depths at which anticipated water, oil or gas formations are expected to be encountered:

Yates	2880'	Oil
Delaware	4540'	Oil
1 st Sand	8410'	Oil
2 nd Sand	9140'	Oil

No other formations are expected to give up oil, gas, or fresh water in measurable quantities. The surface fresh water sands will be protected by setting 13 3/8" casing at 1175' and circulating cement back to surface. All intervals will be isolated by setting 5 1/2" casing to total depth and circulating cement above the base of the 13 3/8" casing.

Marbob plans to drill this well to a total depth of 9800' then log the open hole. At this time it will be decided to run casing and cement the vertical wellbore or to horizontal 1 of 2 zones, either the 2nd Bone Springs Sand @ 9340' or the 1st Bone Springs Sand @ 8560'.
360' *9 5/8" TOC = 3000'* *Per S. Baker* *5-26-08*

Option "A" Vertical
Option "B" Horizontal 2 nd Bone Springs Sand
Option "C" Horizontal 1 st Bone Springs Sand

1. **Proposed Casing Program:**

Option "A"

Hole Size	Interval	OD Casing	New or Used	Wt	Collar	Grade
17 1/2"	0' - 1175'	13 3/8"	New	54.5#	STC	J-55
12 1/4"	1175' - 3300'	9 5/8"	New	36#	STC	J-55
7 7/8"	3300' - 9800'	5 1/2"	New	17#	LTC	N-80

Option "B"

7 7/8"	3300' - 11134'	5 1/2"	New	17#	LTC	N-80
--------	----------------	--------	-----	-----	-----	------

Option "C"

7 7/8"	3300' - 10354'	5 1/2"	New	17#	LTC	N-80
--------	----------------	--------	-----	-----	-----	------

Collapse Design Factor	Burst Design Factor	Tension Design Factor
1.125	1.125	1.6

2. **Proposed Cement Program:**

Option "A"

13 3/8" Surf

Cement to surface with 500 sk "C" Light wt 12.7 ppg yield 1.91 tail in with 200 sk "c" wt 14.8 ppg yield 1.34

9 5/8" Int

Cement to surface with 650 sk "c" Light wt 12.7 ppg yield 1.91 Tail in with 200 sk "c" yield 1.34 wt 14.8 ppg

5 1/2" Prod

Stage 1 350 sk "H" wt 13.0 ppg yield 1.67
Stage 2 450 sk "H" Lite yield 1.91 wt 12.7 Tail in with 200 sk "H" yield 1.67 wt 13.0 DV Tool @ 7000' TOC 3000'

Option "B"

5 1/2" Prod

Cement 1st stage with 250 sk Acid Soluble "H" wt 15.0# yield 2.6. 2nd stage with 550 sk "H" light wt 12.7 ppg yield 1.91 Tail in with 100 sk "H" wt 13.0 yield 1.64 DV Tool 8800 TOC 3000

Option "C"

5 1/2" Prod

Cement 1st stage with 250 sk Acid soluble "H" wt. 15.0# yield 2.6. 2nd stage with 500 sk "H" light Tail in with 100 sk "H" wt 13.0 ppg yield 1.64 DV Tool @ 8000' TOC 3000'

The above cement volumes could be revised pending the caliper measurement from the open hole logs. The top of cement is designed to reach approximately 200' above the 13 3/8" casing shoe. **All casing is new and API approved.**

6. Minimum Specifications for Pressure Control:

Nipple up on 13 3/8" casing with a 2M system test to 1000# with rig pumps. Nipple up on 9 5/8 with a 3M system tested to 3000# with independent tester.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and a 3" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 3000 psi WP rating.

7. Estimated BHP: 4076.8 psi

8. Mud Program: The applicable depths and properties of this system are as follows:

Depth	Type System	Mud Weight	Viscosity (sec)	Waterloss (cc)
0' - 1175'	Fresh Water	8.3 - 8.4	29	N.C.
1175' - 3300'	Brine	10.0	29	N.C.
3300' - 9800'	Cut Brine	9.0	29	N.C.

The necessary mud products for weight addition and fluid loss control will be on location at all times.

9. Auxiliary Well Control and Monitoring Equipment:

- A Kelly cock will be in the drill string at all times.
- A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor at all times.
- Hydrogen Sulfide detection equipment will be in operation after drilling out the 13 3/8" casing shoe until the 5 1/2" casing is cemented. Breathing equipment will be on location upon drilling the 13 3/8" shoe until total depth is reached.

10. Testing, Logging and Coring Program:

- Drill stem tests will be based on geological sample shows.
- The open hole electrical logging program will be:
 - Total Depth to Intermediate Casing: Dual Laterolog-Micro Laterolog and Gamma Ray. Compensated Neutron - Z Density log with Gamma Ray and Caliper.
 - Total Depth to Surface: Compensated Neutron with Gamma Ray
 - No coring program is planned
 - Additional testing will be initiated subsequent to setting the 5 1/2" production casing. Specific intervals will be targeted based on log evaluation, geological sample shows and drill stem tests.


11. Potential Hazards:

a. No abnormal pressures or temperatures are expected. There is no known presence of H₂S in this area. If H₂S is encountered the operator will comply with the provisions of Onshore Oil and Gas Order No. 6. No lost circulation is expected to occur. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. Estimated BHP: 4076.8 psi. No H₂S is anticipated to be encountered.

12. Anticipated starting date and Duration of Operations:

a. Road and location construction will begin after the BLM has approved the APD. Anticipated spud date will be as possible after BLM approval and as soon as a rig will be available. Move in operations and drilling is expected to take 30 days.



Well Site Lay-Out Plat



B-52 Federal #2
330' FNL & 660' FEL
Section 5, T19S - R32E
Lea County, New Mexico

EXHIBIT THREE

2M SYSTEM





2M CHOKE MANIFOLD EQUIPMENT — CONFIGURATION OF CHOKEES

MAY VARY

Exhibit One

3M SYSTEM



3M CHOKE MANIFOLD EQUIPMENT - CONFIGURATION OF CHOKES
MAY VARY

Marbob

B-52 Federal #2

B-52 Federal #2

B-52 Federal #2

Original Hole

Plan: Plan #1


Pathfinder Survey Report

16 April, 2008

FILED

APR 30 PM 3:50

BUREAU OF LAND MGMT
CAMPBELL OFFICE




marbob
energy corporation
Artesia, N.M.



Azimuths to Grid North
True North: -0.30°
Magnetic North: 7.79°

Magnetic Field
Strength: 49216.1snT
Dip Angle: 60.68°
Date: 4/16/2008
Model: IGRF200510





WELL DETAILS: B-52 Federal #2						
Ground Elevation: 3676.00						
RKB Elevation: EST RKB @ 3676.00ft						
Rig Name:						
+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot
0.00	0.00	617257.200	669754.100	32° 41' 44.609 N	103° 46' 53.496 W	

SECTION DETAILS										
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	8852.50	0.00	0.00	8852.50	0.00	0.00	0.00	0.00	0.00	
3	9612.49	90.00	171.95	9339.96	-472.75	66.85	12.00	171.95	477.45	
4	11134.74	90.00	171.95	9340.00	-1980.00	280.00	0.00	0.00	1999.70	PBHL

WELLBORE TARGET DETAILS (MAP CO-ORDINATES)						
Name	TVD	+N/-S	+E/-W	Northing	Easting	Shape
PBHL	9340.00	-1980.00	280.00	615277.200	670034.100	Point

PROJECT DETAILS: B-52 Federal #2
Geodetic System: US State Plane 1927 (Exact solution)
Datum: NAD 1927 (NADCON CONUS)
Ellipsoid: Clarke 1866
Zone: New Mexico East 3001
System Datum: Mean Sea Level
Local North: Grid

Project: B-52 Federal #2
Site: B-52 Federal #2
Well: B-52 Federal #2
Wellbore: Original Hole
Plan: Plan #1 (B-52 Federal #2/Original Hole)



Plan Plan #1 (B-52 Federal #2/Original Hole)
Created By: Mark Freeman Date: 10/02, April 16 2008
Checked: _____ Date: _____

WHS

Pathfinder Survey Report

Company: Marbob	Local Co-ordinate Reference: Well B-52 Federal #2
Project: B-52 Federal #2	TVD Reference: EST RKB @ 3676.00ft
Site: B-52 Federal #2	MD Reference: EST RKB @ 3676.00ft
Well: B-52 Federal #2	North Reference: Grid
Wellbore: Original Hole	Survey Calculation Method: Minimum Curvature
Design: Plan #1	Database: EDM 2003 16 Single User Db

Project: B-52 Federal #2	Map System: US State Plane 1927 (Exact solution)	System Datum: Mean Sea Level
Geo Datum: NAD 1927 (NADCON CONUS)	Map Zone: New Mexico East 3001	

Site: B-52 Federal #2			
Site Position:	From: Map	Northing: 617,257 200ft	Latitude: 32° 41' 44.609 N
Position Uncertainty: 0 00 ft	Easting: 669,754 100ft	Longitude: 103° 46' 53.496 W	Grid Convergence: 0 30 °

Well: B-52 Federal #2			
Well Position:	+N/-S 0 00 ft	Northing: 617,257 200 ft	Latitude: 32° 41' 44.609 N
Position Uncertainty: 0 00 ft	+E/-W 0 00 ft	Easting: 669,754 100 ft	Longitude: 103° 46' 53.496 W
	Wellhead Elevation: ft	Ground Level: 3,676 00 ft	

Wellbore: Original Hole

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF200510	4/16/2008	8 09	60 68	49,216

Design: Plan #1

Audit Notes:

Version: Phase: PLAN Tie On Depth: 0 00

Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)
	0.00	0.00	0 00	171.95

Survey Tool Program		Date
From (ft)	To (ft)	4/16/2008
0 00	11,134.24	
Survey (Wellbore)		Tool Name
Plan #1 (Original Hole)		MWD
		Description
		MWD - Standard

MD (ft)	Inc (°)	Azi (°)	TVD (ft)	N/S (ft)	E/W (ft)	V. Sec (ft)	DLeg (°/100ft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00

WHS

Pathfinder Survey Report

Company: Marbob	Local Co-ordinate Reference: Well B-52 Federal #2
Project: B-52 Federal #2	TVD Reference: EST RKB @ 3676 00ft
Site: B-52 Federal #2	MD Reference: EST RKB @ 3676.00ft
Well: B-52 Federal #2	North Reference: Grid
Wellbore: Original Hole	Survey Calculation Method: Minimum Curvature
Design: Plan #1	Database: EDM 2003 16 Single User Db

Planned Survey

MD (ft)	Inc (°)	Azi (°)	TVD (ft)	N/S (ft)	E/W (ft)	V. Sec (ft)	DLeg (°/100ft)
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00
2,100.00	0.00	0.00	2,100.00	0.00	0.00	0.00	0.00
2,200.00	0.00	0.00	2,200.00	0.00	0.00	0.00	0.00
2,300.00	0.00	0.00	2,300.00	0.00	0.00	0.00	0.00
2,400.00	0.00	0.00	2,400.00	0.00	0.00	0.00	0.00
2,500.00	0.00	0.00	2,500.00	0.00	0.00	0.00	0.00
2,600.00	0.00	0.00	2,600.00	0.00	0.00	0.00	0.00
2,700.00	0.00	0.00	2,700.00	0.00	0.00	0.00	0.00
2,800.00	0.00	0.00	2,800.00	0.00	0.00	0.00	0.00
2,900.00	0.00	0.00	2,900.00	0.00	0.00	0.00	0.00
3,000.00	0.00	0.00	3,000.00	0.00	0.00	0.00	0.00
3,100.00	0.00	0.00	3,100.00	0.00	0.00	0.00	0.00
3,200.00	0.00	0.00	3,200.00	0.00	0.00	0.00	0.00
3,300.00	0.00	0.00	3,300.00	0.00	0.00	0.00	0.00
3,400.00	0.00	0.00	3,400.00	0.00	0.00	0.00	0.00
3,500.00	0.00	0.00	3,500.00	0.00	0.00	0.00	0.00
3,600.00	0.00	0.00	3,600.00	0.00	0.00	0.00	0.00
3,700.00	0.00	0.00	3,700.00	0.00	0.00	0.00	0.00
3,800.00	0.00	0.00	3,800.00	0.00	0.00	0.00	0.00
3,900.00	0.00	0.00	3,900.00	0.00	0.00	0.00	0.00
4,000.00	0.00	0.00	4,000.00	0.00	0.00	0.00	0.00
4,100.00	0.00	0.00	4,100.00	0.00	0.00	0.00	0.00
4,200.00	0.00	0.00	4,200.00	0.00	0.00	0.00	0.00
4,300.00	0.00	0.00	4,300.00	0.00	0.00	0.00	0.00
4,400.00	0.00	0.00	4,400.00	0.00	0.00	0.00	0.00
4,500.00	0.00	0.00	4,500.00	0.00	0.00	0.00	0.00
4,600.00	0.00	0.00	4,600.00	0.00	0.00	0.00	0.00
4,700.00	0.00	0.00	4,700.00	0.00	0.00	0.00	0.00
4,800.00	0.00	0.00	4,800.00	0.00	0.00	0.00	0.00
4,900.00	0.00	0.00	4,900.00	0.00	0.00	0.00	0.00
5,000.00	0.00	0.00	5,000.00	0.00	0.00	0.00	0.00
5,100.00	0.00	0.00	5,100.00	0.00	0.00	0.00	0.00
5,200.00	0.00	0.00	5,200.00	0.00	0.00	0.00	0.00
5,300.00	0.00	0.00	5,300.00	0.00	0.00	0.00	0.00
5,400.00	0.00	0.00	5,400.00	0.00	0.00	0.00	0.00
5,500.00	0.00	0.00	5,500.00	0.00	0.00	0.00	0.00

WHS

Pathfinder Survey Report

Company:	Marbob	Local Co-ordinate Reference:	Well B-52 Federal #2
Project:	B-52 Federal #2	TVD Reference:	EST RKB @ 3676.00ft
Site:	B-52 Federal #2	MD Reference:	EST RKB @ 3676.00ft
Well:	B-52 Federal #2	North Reference:	Grd
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 2003.16 Single User Db

Planned Survey

MD (ft)	Inc (°)	Azi (°)	TVD (ft)	N/S (ft)	E/W (ft)	V. Sec (ft)	DLeg (°/100ft)
5,600.00	0.00	0.00	5,600.00	0.00	0.00	0.00	0.00
5,700.00	0.00	0.00	5,700.00	0.00	0.00	0.00	0.00
5,800.00	0.00	0.00	5,800.00	0.00	0.00	0.00	0.00
5,900.00	0.00	0.00	5,900.00	0.00	0.00	0.00	0.00
6,000.00	0.00	0.00	6,000.00	0.00	0.00	0.00	0.00
6,100.00	0.00	0.00	6,100.00	0.00	0.00	0.00	0.00
6,200.00	0.00	0.00	6,200.00	0.00	0.00	0.00	0.00
6,300.00	0.00	0.00	6,300.00	0.00	0.00	0.00	0.00
6,400.00	0.00	0.00	6,400.00	0.00	0.00	0.00	0.00
6,500.00	0.00	0.00	6,500.00	0.00	0.00	0.00	0.00
6,600.00	0.00	0.00	6,600.00	0.00	0.00	0.00	0.00
6,700.00	0.00	0.00	6,700.00	0.00	0.00	0.00	0.00
6,800.00	0.00	0.00	6,800.00	0.00	0.00	0.00	0.00
6,900.00	0.00	0.00	6,900.00	0.00	0.00	0.00	0.00
7,000.00	0.00	0.00	7,000.00	0.00	0.00	0.00	0.00
7,100.00	0.00	0.00	7,100.00	0.00	0.00	0.00	0.00
7,200.00	0.00	0.00	7,200.00	0.00	0.00	0.00	0.00
7,300.00	0.00	0.00	7,300.00	0.00	0.00	0.00	0.00
7,400.00	0.00	0.00	7,400.00	0.00	0.00	0.00	0.00
7,500.00	0.00	0.00	7,500.00	0.00	0.00	0.00	0.00
7,600.00	0.00	0.00	7,600.00	0.00	0.00	0.00	0.00
7,700.00	0.00	0.00	7,700.00	0.00	0.00	0.00	0.00
7,800.00	0.00	0.00	7,800.00	0.00	0.00	0.00	0.00
7,900.00	0.00	0.00	7,900.00	0.00	0.00	0.00	0.00
8,000.00	0.00	0.00	8,000.00	0.00	0.00	0.00	0.00
8,100.00	0.00	0.00	8,100.00	0.00	0.00	0.00	0.00
8,200.00	0.00	0.00	8,200.00	0.00	0.00	0.00	0.00
8,300.00	0.00	0.00	8,300.00	0.00	0.00	0.00	0.00
8,400.00	0.00	0.00	8,400.00	0.00	0.00	0.00	0.00
8,500.00	0.00	0.00	8,500.00	0.00	0.00	0.00	0.00
8,600.00	0.00	0.00	8,600.00	0.00	0.00	0.00	0.00
8,700.00	0.00	0.00	8,700.00	0.00	0.00	0.00	0.00
8,800.00	0.00	0.00	8,800.00	0.00	0.00	0.00	0.00
8,862.50	0.00	0.00	8,862.50	0.00	0.00	0.00	0.00
8,875.00	1.50	171.95	8,875.00	-0.16	0.02	0.16	12.00
8,900.00	4.50	171.95	8,899.96	-1.46	0.21	1.47	12.00
8,925.00	7.50	171.95	8,924.82	-4.04	0.57	4.08	12.00
8,950.00	10.50	171.95	8,949.51	-7.92	1.12	8.00	12.00
8,975.00	13.50	171.95	8,973.96	-13.06	1.85	13.19	12.00
9,000.00	16.50	171.95	8,998.11	-19.47	2.75	19.66	12.00
9,025.00	19.50	171.95	9,021.88	-27.12	3.83	27.39	12.00
9,050.00	22.50	171.95	9,045.22	-35.99	5.09	36.34	12.00
9,075.00	25.50	171.95	9,068.05	-46.05	6.51	46.51	12.00
9,100.00	28.50	171.95	9,090.33	-57.29	8.10	57.86	12.00

WHS
Pathfinder Survey Report

Company: Marbob	Local Co-ordinate Reference: Well B-52 Federal #2
Project: B-52 Federal #2	TVD Reference: EST RKB @ 3676.00ft
Site: B-52 Federal #2	MD Reference: EST RKB @ 3676.00ft
Well: B-52 Federal #2	North Reference: Grd
Wellbore: Original Hole	Survey Calculation Method: Minimum Curvature
Design: Plan #1	Database: EDM 2003.16 Single User Db

Planned Survey

MD (ft)	Inc (°)	Azi (°)	TVD (ft)	N/S (ft)	E/W (ft)	V. Sec (ft)	DLeg (°/100ft)
9,125.00	31.50	171.95	9,111.97	-69.67	9.85	70.36	12.00
9,150.00	34.50	171.95	9,132.94	-83.15	11.76	83.97	12.00
9,175.00	37.50	171.95	9,153.16	-97.69	13.82	98.67	12.00
9,200.00	40.50	171.95	9,172.59	-113.27	16.02	114.40	12.00
9,225.00	43.50	171.95	9,191.17	-129.83	18.36	131.12	12.00
9,250.00	46.50	171.95	9,208.84	-147.33	20.84	148.80	12.00
9,275.00	49.50	171.95	9,225.57	-165.73	23.44	167.38	12.00
9,300.00	52.50	171.95	9,241.30	-184.96	26.16	186.80	12.00
9,325.00	55.50	171.95	9,255.99	-204.99	28.99	207.03	12.00
9,350.00	58.50	171.95	9,269.61	-225.74	31.92	227.99	12.00
9,375.00	61.50	171.95	9,282.10	-247.18	34.95	249.64	12.00
9,400.00	64.50	171.95	9,293.45	-269.23	38.07	271.91	12.00
9,425.00	67.50	171.95	9,303.62	-291.84	41.27	294.75	12.00
9,450.00	70.50	171.95	9,312.58	-314.95	44.54	318.08	12.00
9,475.00	73.50	171.95	9,320.30	-338.49	47.87	341.86	12.00
9,500.00	76.50	171.95	9,326.77	-362.40	51.25	366.00	12.00
9,525.00	79.50	171.95	9,331.97	-386.61	54.67	390.45	12.00
9,550.00	82.50	171.95	9,335.88	-411.05	58.13	415.14	12.00
9,575.00	85.50	171.95	9,338.49	-435.67	61.61	440.00	12.00
9,600.00	88.50	171.95	9,339.80	-460.39	65.11	464.97	12.00
9,612.49	90.00	171.95	9,339.96	-472.75	66.85	477.45	12.00
9,700.00	90.00	171.95	9,339.97	-559.40	79.11	564.96	0.00
9,800.00	90.00	171.95	9,339.97	-658.41	93.11	664.96	0.00
9,900.00	90.00	171.95	9,339.97	-757.43	107.11	764.96	0.00
10,000.00	90.00	171.95	9,339.97	-856.44	121.11	864.96	0.00
10,100.00	90.00	171.95	9,339.98	-955.46	135.12	964.96	0.00
10,200.00	90.00	171.95	9,339.98	-1,054.47	149.12	1,064.96	0.00
10,300.00	90.00	171.95	9,339.98	-1,153.49	163.12	1,164.96	0.00
10,400.00	90.00	171.95	9,339.98	-1,252.50	177.12	1,264.96	0.00
10,500.00	90.00	171.95	9,339.99	-1,351.52	191.12	1,364.96	0.00
10,600.00	90.00	171.95	9,339.99	-1,450.53	205.13	1,464.96	0.00
10,700.00	90.00	171.95	9,339.99	-1,549.55	219.13	1,564.96	0.00
10,800.00	90.00	171.95	9,339.99	-1,648.56	233.13	1,664.96	0.00
10,900.00	90.00	171.95	9,339.99	-1,747.58	247.13	1,764.96	0.00
11,000.00	90.00	171.95	9,340.00	-1,846.59	261.13	1,864.96	0.00
11,100.00	90.00	171.95	9,340.00	-1,945.61	275.14	1,964.96	0.00
11,134.74	90.00	171.95	9,340.00	-1,980.00	280.00	1,999.70	0.00


WHS
Pathfinder Survey Report

Company:	Marbob	Local Co-ordinate Reference:	Well B-52 Federal #2
Project:	B-52 Federal #2	TVD Reference:	EST RKB @ 3676 00ft
Site:	B-52 Federal #2	MD Reference:	EST RKB @ 3676 00ft
Well:	B-52 Federal #2	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 2003.16 Single User Db

Targets									
Target Name	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- hit/miss target	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(ft)		
PBHL	0.00	0.00	9,340 00	-1,980 00	280 00	615,277 200	670,034 100	32° 41' 25 002 N	103° 46' 50 340 W
- plan hits target									
- Point									

Checked By: _____	Approved By: _____	Date: _____
-------------------	--------------------	-------------

LOCATION VERIFICATION MAP



SCALE: 1" = 2000'

CONTOUR INTERVAL: 10'
GREENWOOD LAKE, NM

SEC. 5 TWP. 19-S RGE. 32-E

SURVEY N.M.P.M.

COUNTY LEA STATE NEW MEXICO

DESCRIPTION 330' FNL & 660' FEL


ELEVATION 3676'

OPERATOR MARBOB ENERGY CORPORATION

LEASE B-52 FEDERAL

U.S.G.S. TOPOGRAPHIC MAP
GREENWOOD LAKE, NM

Existing Roads



PROVIDING SURVEYING SERVICES
SINCE 1946
JOHN WEST SURVEYING COMPANY
412 N. DAL PASO
HOBBS, N.M. 88240
(505) 393-3117

EXHIBIT #2




EXHIBIT #4
 ● B-52 FEDERAL #2

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Marbob Energy
LEASE NO.:	NMNM118720
WELL NAME & NO.:	B 52 Federal No 2
SURFACE HOLE FOOTAGE:	330' FNL & 660' FEL
BOTTOM HOLE FOOTAGE:	
LOCATION:	Section 5, T. 19 S., R 32 E., NMPM
COUNTY:	Lea County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
 - Lesser Prairie Chicken
- Construction**
 - Notification
 - Topsoil
 - Reserve Pit
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- Road Section Diagram**
- Drilling**
- Production (Post Drilling)**
 - Well Structures & Facilities
- Interim Reclamation**
- Final Abandonment/Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 15 through June 15 annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (505) 234-5972 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall stockpile the topsoil of the well pad. The topsoil to be stripped is approximately 8 inches in depth. The topsoil shall not be used to backfill the reserve pit and will be used for interim and final reclamation.

C. RESERVE PITS

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

If the operator elects to surface the access road and/or well pad, mineral materials extracted during construction of the reserve pit may be used for surfacing the well pad and access road and other facilities on the lease.

Payment shall be made to the BLM prior to removal of any additional federal mineral materials from any site other than the reserve pit. Call the Carlsbad Field Office at (505) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed thirty (30) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning


Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall be constructed on all blind curves. Turnouts shall conform to the following diagram:



Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400' + 100'}{4\%} = 200' \text{ lead-off ditch interval}$$

Culvert Installations

Appropriately sized culvert(s) shall be installed at the deep waterway channel flow crossing.

Cattleguards

An appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s).

Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations.

A gate shall be constructed and fastened securely to H-braces.

Fence Requirement


Where entry is required across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting.

The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Figure 1 – Cross Sections and Plans For Typical Road Sections



VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of **4 hours** in advance for a representative to witness:

- a. Spudding well
- b. Setting and/or Cementing of all casing strings
- c. BOP/BOPE tests

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,
(575) 393-3612

1. **A Hydrogen Sulfide (H₂S) Drilling Plan should be activated 500 feet prior to drilling into the Yates Formation. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

B. CASING

Changes to the approved APD casing and cement program require submitting a sundry and receiving approval prior to work.

Centralizers required on surface casing as per Onshore Order 2.III.B.1.f

Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

**Possible lost circulation in Artesia Group
Possible H₂O/brine flows in Artesia Group & Salado**

1. The 13-3/8 inch surface casing shall be set at **approximately 1150 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.**
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement).
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:
 Cement to surface. If cement does not circulate see B.1.a-d above.
3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - a. **First stage to DV tool, cement shall:**
 Cement to circulate. If cement does not circulate, contact the appropriate BLM office, before proceeding with second stage cement job.
 - b. **Second stage above DV tool, cement shall:**
 Cement should tie-back at least 200 feet into previous casing string. **Operator shall provide method of verification.**

Marbob plans to drill this well to 9800' TD then log the open hole. At this time it will be decided to run and cement casing for a vertical wellbore completion or to horizontal 1 of 2 zones, either the 2nd Bone Spring Sand @ 9340' or the 1st Bone Spring Sand @ 8560'. Centralizers required on horizontal leg, must be type for horizontal service and minimum of one every other joint.

4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. The appropriate BLM office shall be notified a minimum of **4 hours** in advance for a representative to witness the tests.
 - a. The tests shall be done by an independent service company.
 - b. The results of the test shall be reported to the appropriate BLM office.
 - c. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
 - d. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.
 - e. A variance to test the surface casing and BOP/BOPE (**entire system**) to the reduced pressure of 1000 psi with the rig pumps is approved.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

LB 5/23/08

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Containment Structures

The containment structure shall be constructed to hold the capacity of the entire contents of the largest tank, plus 24 hour production, unless more stringent protective requirements are deemed necessary by the Authorized Officer.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color Shale Green, Munsell Soil Color Chart # 5Y 4/2

IX. INTERIM RECLAMATION & RESERVE PIT CLOSURE

A. INTERIM RECLAMATION

If the well is a producer, interim reclamation shall be conducted on the well site in accordance with the orders of the Authorized Officer. The operator shall submit a Sundry Notices and Reports on Wells (Notice of Intent), Form 3160-5, prior to conducting interim reclamation.

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

The operators should work with BLM surface management specialists to devise the best strategies to reduce the size of the location. Any reductions should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

Seed Mixture for LPC Sand/Shinnery Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

**Four-winged Saltbush 5lbs/A

* This can be used around well pads and other areas where caliche cannot be removed.

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed
(Insert Seed Mixture Here)

X. FINAL ABANDONMENT & REHABILITATION REQUIREMENTS

Upon abandonment of the well and/or when the access road is no longer in service the Authorized Officer shall issue instructions and/or orders for surface reclamation and restoration of all disturbed areas.

On private surface/federal mineral estate land the reclamation procedures on the road and well pad shall be accomplished in accordance with the private surface land owner agreement.