

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

| | | | | | |
|---|--|---|-------------------------------------|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | <input checked="" type="checkbox"/> | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF PLUGGING WELL | | REPORT ON RECOMPLETION OPERATION | | REPORT ON (Other) | |

June 19, 1953
(Date)

Tatum, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation
(Company or Operator)

H. C. Pacey "A"
(Lease)

Creekmore Drilling Company
(Contractor)

Well No. 4 in the NW/4 NE/4 of Sec. 14

T. 12-S, R. 32-N, NMPM, East Caprock - Devonian Pool, Lea County.

The Dates of this work were as follows: June 18, 1953

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan (~~was~~) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11,255' Total Depth. Lins. Finished drilling 7-7/8" hole @ 2:30 PM on 6/13/53. Ran Schlumberger surveys. Ran a total of 320 jts of 5/8" OD casing and set @ 11,295' and cement with 600 sacks of cement. Pumped plug down to 11,114' @ 12:30 AM on 6/14/53. Max. pump pressure was 2000#. Ran temperature survey test - top of cement outside of 5-1/2" OD casing @ 7667' or 86.1% fill. After WOC for 24 hours tested 5-1/2" OD casing before drilling cement w/ 1000# for 1/2 hour - no pressure drop. Drilled cement from 11,114' to 11,295' and washed to 11,255'. Tested 5-1/2" OD casing after drilling cement w/ 1000# for 1/2 hour - no pressure drop. Continued with completion operations.

Witnessed by R. Q. Swanson (Name) Amerada Petroleum Corporation (Company) Farm Boss (Title)

Approved: OIL CONSERVATION COMMISSION

Ray Yachrough (Name)

Oil & Gas Inspector

(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: [Signature]

Position: Assistant District Superintendent

Representing: Amerada Petroleum Corporation

Address: Roswell Star Route Tatum, New Mex.

JUN 22 1953

(Date)

Handwritten text at the top of the page, possibly a header or title.

Handwritten text in the upper middle section of the page.

Handwritten text in the middle section of the page.

Handwritten text in the lower middle section of the page.

Handwritten text in the lower section of the page.

Handwritten text at the bottom of the page.