

PLEASE TYPE OFFICIAL DESIGNATION OF OFFICIAL

When an application for a permit to drill a well is received, the District Engineer will issue a permit to drill and the permittee shall comply with the conditions of the permit. The District Engineer will issue a permit to drill and the permittee shall comply with the conditions of the permit. The District Engineer will issue a permit to drill and the permittee shall comply with the conditions of the permit.

GENERAL

1. Any drilling, testing or production shall be permanently marked on a conspicuous place with the name of the well, the name of the owner, the well number, and location. The marking shall be made as soon as possible after the drilling is completed.

2. Any change in the design, location, or conditions of approval must be written approval of the District Engineer BEFORE the change is made.

3. Unless otherwise specified, or if approved to drill, the production testing of a well must be set at the top of the gas zone. The completion shall be made with a permeable gas oil ratio.

4. Before work is started, written approval must be obtained, unless other acceptable arrangements have been made with the District Engineer, and after work is completed results must be reported to the U. S. Geological Survey by submitting complete information in triplicate on form G-311a, covering:

- a. Method of measuring, including proposed data and method of testing water show-off.
- b. Drilling tests or perforating.
- c. Casing alternatives, packer setting, or repairs of any kind.
- d. Shooting, acid treatment, deepening or plugging back.
- e. Casing installations.
- f. Drilling of water wells.

5. Monthly report of operations in duplicate, on form G-329, must be submitted promptly each month beginning with beginning of the first well on a lease and continuing until approved abandonment of all drilling and producing operations.

6. Log, in duplicate, on form G-330, must be submitted within 10 days of reaching temporary or permanent drilling depth. Copies of all electrical logs, sample cutting logs, drilling time logs, and any other well information not given on the standard form should be attached to same.

7. Separate applications to drill any water well on federal land is required, and special procedure is necessary for abandonment of any well having a desirable water supply.

8. All wells and lease premises shall be maintained in first class condition with due regard to safety, conservation, appearance, and refuse disposal.

9. The notice of intention to drill any well is rescinded without further notice if drilling is not started within 90 days of approval.

10. Cement must be allowed to set a minimum of 72 hours on all strings of casing prior to drilling the plug, except for modification provided by the Supervisor's order dated March 15, 1947, copy of which will be furnished on request.

SPECIAL (None, if so indicated.)