

50-025-20420

WC COUNTY Lea FIELD Wildcat STATE N.M. NO. MAP  
 OPR. Coastal States Gas Producing Company  
 NO. 1 LSE Pure-State  
 SEC. 11 T. 9S BLK. 33E SUR. CO-ORD.  
 LOC. 660' fr S Line & 2310' fr W Line of Sec. EL. 43695

SPUD.	MI.	FROM	COMP.	FORMATION	DATE	FORMATION	DATE
1-23-63				P&A			
				LOG:			
				Yates	2638		
				SA	3849		
CSG. & SX.				Glor	5282		
13	3/8"	432'	400	Tubb	6777		
8	5/8"	4725'	210	Abo	7647		
TBG. DEPTH				Wolfc	8770		
LOGS EL GR RA IND HC A				Bo."C"	9588		
				TD	12478'		
PROD INT.				IP			
(DAILY RATE)				BS&W	GH	GOR	GTY C. P. T. P. HRS. TEST

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.  
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sharp Drlg. Co. PROP DEPTH 12,500' TYPE DATE

- 1-24-63 F.R. 1-17-63, Devonian.
- 1-28-63 Contractor - Sharp Drlg. Co., PD 12,500' RT.
- 2-4-63 AMENDED FOOTAGE: was 660' FSL & 1980' FWL of Sec.
- 2-11-63 Drlg. 3630'.
- 2-18-63 Drlg. 4419'.
- 2-25-63 TD 5914', fshg.
- 3-4-63 Drlg. 7850' sh.
- 3-11-63 Drlg. 8796' dolo.
- 3-18-63 DST 8695-8740', open 1 hr, rec 360' DM, FP 130-215#, 30" FSIP 3975#.
- 3-4-63 Drlg. 9339' ls.
- 3-11-63 DST 9046-56', mis-run.
- 3-18-63 DST 9046-66', mis-run.
- 3-11-63 Coring @ 9625'.
- 3-18-63 Cored 9497-9533', rec 17.5' ls. & sh., w/NS.
- 3-18-63 Cored 9555-9571', rec 14.5' ls. & sh., w/sli. poro.
- 3-18-63 9555-66', bldg. wtr.
- 3-18-63 Drlg. 9858'.

Coastal States Gas Producing Co., #1 Pure-State - Sec. 11-  
Wildcat 9S-33E

-cont.-

Cored 9604-27', rec 23' dense ls. & sh., NS.  
DST 9592-9627', open 1 hr, rec 30' DM, FP 40-40#,  
45" FSIP 40#.  
DST 9708-25', open 1 hr, rec 15' DM, FP 50-50#,  
45" FSIP 95#.

3-25-63 Drlg. 10550' ls.  
4-1-63 Drlg. 11032'.  
4-8-63 Drlg. 11568'.  
4-15-63 TD 11826', SDO.  
4-22-63 TD 11826', SDO.  
4-29-63 TD 11826', SDO.  
5-6-63 TD 12478', PLUGGED & ABANDONED.  
(Holding for complete information).  
9-3-63 TD 12478', Completion Reported.  
DST 12061-80', open 1 hr, rec 2500' WB + 7680'  
salt wtr, FP 2160-4210#, 30" FSIP 4225#.

WLT @ 9046', rec 1500 cc's wtr, 63" SIP 3300#.  
WLT 9480-83', dry test.  
WLT 9544-47', rec .08 CFG, pressures less than  
50#.  
WLT @ 10041', dry test.  
WLT 10811-814', dry test.  
WLT 10950-953', dry test.  
LOG TOPS - CONTINUED -  
Mississippian 11790', Devonian 12462'.