

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
K-5775

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL  GAS WELL  OTHER

2. Name of Operator  
R. L. Burns Corp.

3. Address of Operator  
3990 First National Bank Building, Dallas, Texas 75202

4. Location of Well  
UNIT LETTER J 1980 FEET FROM THE S LINE AND 1980 FEET FROM  
THE E LINE, SECTION 11 TOWNSHIP 9-S RANGE 33E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
4346.4' Gr.

7. Unit Agreement Name  
J

8. Farm or Lease Name  
State '11'

9. Well No.  
1

10. Field and Pool, or Wildcat  
Vada Penn

12. County  
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to plug and abandon this well as follows:

Set cement retainer on tubing at 7500' and pump 100 sx cement below retainer, and 25 sx above retainer.

Find free point in 5-1/2" casing above cement @ 6410'.

Cut off 5-1/2" and spot 200' cement plug at cut off, keeping hole full of mud.

Spot 200' cement plug across shoe of 8-5/8" casing at 3890'.

Spot 100' cement plug inside 8-5/8" casing at 2300' top of salt.

Spot 15' cement plug at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John J. [Signature] TITLE Vice President DATE March 9, 1977

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:  
Expires 9/14/77

MAR 14 1977

RECEIVED

MAY 1 1977

OIL CONSERVATION BOARD  
SUSSEX, N. H.