

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Nov 4 11 54 AM '65

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-10130	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Champlin Petroleum Company		8. Farm or Lease Name Hondo-State
3. Address of Operator P. O. Box 1797, Midland, Texas		9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>7-S</u> RANGE <u>33-E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4420 GR		12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The well originally perforated in the San Andres 2 shots per ft. from 4299 to 4304, 4320-28, 4333-36, 4342-47'. Acidize w/2500 gal. of acid. Well had declined below the daily allowable. Pulled rods and tubing out of hole. Set Baker cast iron bridge plug at 4470'. Perf. 2 holes at 4188, 4261, 4277, 4282, 4417, & 4429'. Acidize perf. from 4188, 4261, 4277, 4282, 4417, & 4429 w/2500 gal. of acid. Frac. all perf. w/40,000 gal. San Andres water, 40,000# 20-40 sand, using rock salt for blocking agent. Swab water back. Pumping now 60 barrels per day, 28 barrels water, G.O.R. 1528.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. N. Brown H. N. Brown TITLE District Superintendent DATE November 3, 1965

APPROVED BY [Signature] TITLE Engineer District 1 DATE NOV 5 1965

CONDITIONS OF APPROVAL, IF ANY: