

COUNTY Roosevelt FIELD Milnesand-San Andres STATE N.M. NO. 30-041-10207

OPR Sun Oil Company MAP

NO. 3 LSE Cosby, G. M.

SEC. 12 T. 8S BLK. 34E SUR.

LOC. 990' fr N Line & 330' fr E Line of Sec. CO-ORD.

MI. FROM

SPUD. 6-17-63 COMP. 8-5-63 CLASS. EL. 42698

IRT	4000 Ac., SOF	LOG:	DATUM	FORMATION	DATUM
	<u>20,000 + 20,000# sd.</u>	<u>Anhy 2126</u>			
	<u>8 5/8" 350' 250</u>	<u>Yates 2655</u>			
	<u>4 1/2" 4700' 250</u>	<u>SA 3836</u>			
		<u>SA Porc 4558</u>			

TBG.	DEPTH	SIZE	LOGS	EL	GR	RA	IND	HC	A

PROD INT. (DAILY RATE) IP TD 4700' PB 4644'

4620-38' Pump 77 EO tr. BS&W GH GOR GTY C.P. T.P. HRS. TEST

(San Andres) wtr. 1291 30.5 24'

Distribution limited and publication prohibited by subscribers' agreement.  
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 4550' TYPE

- 4-17-63 F.R. 3-7-63, San Andres. PD 4550'.
- 6-24-63 AMENDED FOOTAGE: Was 660' FN&EL of Section.
- 7-1-63 Drlg. 4045' anhy.
- 7-8-63 TD 4700' dolo., PB 4677', WOC.
- TD 4700' dolo., PB 4677', prep to sq.
- Perf 10/4652-57', swbd dry.
- Tr. 500 Ac., swbd 120 B Salt wtr, tr. oil, in 5 1/2 hrs, swbd 2 BO + 177 E Salt Wtr in 12 hrs.
- 7-15-63 TD 4700', PB 4644', swbg.
- Set ret. @ 4644' & sq. perfs 4652-57' w/300 sx.
- Perf 4/4620-22', 6/4624-27', 10/4628-33', 4/4636-38', tr. 2000 Ac., swbd 76 BLW/2 1/2 hrs, w/tr. oil.
- 7-22-63 Swbd 16.5 BO + 93.5 B Salt Wtr/12 hrs.
- TD 4700' dolo., PB 4644', swbg.
- Swbd 26 BO, w/tr. wtr in 8 hrs; re-treated 2000 Ac., swbd 40 BLO + 20 BW/1 hr.
- SOF 20,000 gals + 20,000# sd.

Sun Oil Company, #3 Cosby, G. M. - Sec. 12-8S-34E

7-29-63 TD 4700', PB 4644', ppg. load. (-437).  
8-5-63 TD 4700', PB 4644', WO Potential.  
8-12-63 TD 4700', PB 4644', COMPLETED.