

COUNTY	ROOSEVELT		FIELD	Chaveroo		STATE	NM	
OPR	CHAMFLIN PETROLEUM CO.					MAP		
	9 State							
	Sec. 32, T-7-S, R-33-E					CO-ORD		
	1980' FNL, 1980' FWL of Sec.					MX 10444		
	Spd 3-12-66		CLASS			EL		
	Cmp 4-3-66		FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING								
	8 5/8"	384'	200					
	4 1/2"	4500'	300					
LOGS	EL	GR	RA	IND	HC	A		
			TD 4500', PBD 4473'					

IP San Andres Perfs 4244-4447' Pmpd 52 BOPD + 91 BW. Pot. Based on 24 hr test, gravity 24.6, Gas Volume 30 MCFGPD.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Sitton & Norton	PROP DEPTH	4500'	TYPE
DATE				

F.R. 2-10-66
PD 4500' - SA
Contractor - Sitton & Norton

3-14-66 Drig. 2420'.
3-21-66 Drig. 4152'.
3-28-66 TD 4500', RU Pump.
Perf @ 4244', 4275', 4281', 4298', 4319',
4329', 4337', 4363', 4418', 4431', 4447'
Ac (4244-4447') 2500 gals.
Frac (4244-4447') 50,000 gals wtr +
40,000# sd.

4-4-66 TD 4500', PBD 4473', pmpg load. (-540 BLW)
4-11-66 TD 4500', PBD 4473', tstg on pump.
Pmpd 75 EF (38% oil) in 24 hrs.
4-18-66 TD 4500', PBD 4473', COMPLETE.
LOG TOP: Yates 2322', Queen 3000',
San Andres 3568'.