

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

HOBBS OFFICE O. C. C.  
APR 25 8 50 AM '66

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee   
5. State Oil & Gas Lease No.  
**E - 1369**

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name -
2. Name of Operator <b>Shelly Oil Company</b>	8. Farm or Lease Name <b>Hobbs "T" T.B. #2</b>
3. Address of Operator <b>Box 730 - Hobbs, New Mexico</b>	9. Well No. <b>17</b>
4. Location of Well UNIT LETTER <b>2A</b> <b>660</b> FEET FROM THE <b>North</b> LINE AND <b>640</b> FEET FROM THE <b>East</b> LINE, SECTION <b>35</b> TOWNSHIP <b>7-S</b> RANGE <b>33-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Chabasco San Andres</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4346' RT</b>	12. County <b>Roosevelt</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Reached total depth at 12:30 p.m. April 17, 1966. Set 139 jts (4488') of new 4-1/2" OD 10.5# GR SS J-55 R-2 RT & C casing at 4500'. Cemented with 350 sacks of cement by the pump & plug process. Plug down at 7:15 p.m. April 18, 1966. Temperature survey indicated cement outside of 4-1/2" OD casing at 3280' from the surface. W.D.C. 24 hours. Pressured casing up to 600# for 30 minutes and casing tested OK. Did not drill out cement plug. P.D.S.B. 4463'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

(ORIGINAL SIGNED) **H. E. Aab**

**District Superintendent**

**April 22, 1966**

SIGNED \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: