

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYBUREAU OF LAND MANAGEMENT  
OFFICE OF THE DIRECTOR  
WASHINGTON, D.C.Form approved.  
Budget Bureau No. 42-B1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 23018

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "J"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Bluitt (Wolfcamp)

11. SEC., T., R., M., OR BEK. AND  
SURVEY OR AREA

Sec. 10, 8-S, 37-E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

H. L. Brown, Jr.

3. ADDRESS OF OPERATOR

P. O. Box 2237, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below  
At surface

1650' FEL and 1650' FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4039 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PUMP OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLAYS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

OTHER

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Running casing

NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Include state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On Sept. 16, 1979, ran 13 jts of 12-3/4" OD csg with guide shoe and baffle plate one jt. up (481.52'). Set at 481', cemented with 268 sx BJ lite, 2% gel, 2% CaCl<sub>2</sub>, 1/4#/sx celoflake, and 200 sx Class C, 2% CaCl<sub>2</sub>, full returns. Circulated 60 sx to surface. Bumped plug at 9:58 p.m.

On Sept. 24, 1979, ran 3-5/8" csg (33 jts, 32#, K-55, ST and 60 jts 24#, k-55 ST), guide shoe on bottom 4 jts, and set at 3756'. Cemented with 1100 sx BJ lite, 1/4#/sx celoflake, 6% gel, 10#/sx NaCl, and 200 sx Class C, 2% CaCl<sub>2</sub>. Did not bump plug. Circulated 198 sx to surface.

On Oct. 31, 1979, ran 4-1/2" csg, (2 jts. 11.60# K-55 ST, float collar, and 195 jts. 9.50#, 10.50#, and 11.60# K-55 ST&C), set at 8458'. Cemented with 800 sx Class H 50-50 poz, 2% gel, 6#/sx NaCl (last 300 sx had 0.7% D-19.) Top of cement at 6425'.

18. I hereby certify that the foregoing is true and correct.

SIGNED

Jill W. White

TITLE Prod. Asst.

DATE Mar. 3, 1980

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

U. S. GEOLOGICAL SURVEY  
MIDLAND, NEW MEXICO

\*See Instructions on Reverse Side