

COUNTY CHAVES		FIELD Tobac-Pennsylvanian STATE N.M.	
OPR THE ATLANTIC REFG. COMPANY		MAP	
5 Mona-Federal		CO-ORD	
Sec. 17, T-8-S, R-33-E			
1980' fr N & E Lines of Sec.			
Spud 2-9-65		CLASS	
Comp 4-11-65		E	
		FORMATION	DATUM
CSG & SX - TUBING		LOG:	
13 3/8"	392' 350	Anhy 1826	
8 5/8"	3509' 835	Glor 4974	
5 1/2"	9039' 400	Abo 7262	
		Bough "C"	
		8909	
LOGS EL GR RA IND HC A			
		TD 9040'	

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 9100' TYPE

F. R. 2-11-65.
PD 9100' - Pennsylvanian.
2-15-65 TD 3570', WOC.
2-22-65 Drlg. 6665'.
3-1-65 Drlg. 8080'.
3-8-65 Drlg. 8980'.
3-15-65 TD 9040', PB 9006', swbg.
Perf. 8979-85', 8992-98' W/2 SPF.
Attempt to Ac. W/1000 gals. would not break.
Set BP @ 8960'.
Perf. 8911-17', 8921-26' W/2 SPF.
Ac. 1000 gals.
Re-Perf. 8911-17', 8921-26' W/2 SPF.
Swbd. & Flwd. 2 BAW + 10 BNO/2 hrs.
Re-Ac. 2500 gals.
Swbd. 60 BAW + 35 BLO + 97 BNO/24 hrs.

3-22-65 TD 9040', PED 9006', SI.
 Re-Ac. 5000 gals. 8911-26'
 Swbd 45 BO + 47 BFW in 25½ hrs.
3-29-65 TD 9040', PED 9006', swbg load.
 Re-Ac. 20,000 gals 8911-26'.
 Swbd 21 BLO + 4 BAW/10½ hrs (-443 BLO).
4-5-65 TD 9040', PED 9006', swbg.
 Swbd 8 BLO + 22 BAW in 4 hrs.
4-12-65 TD 9040', PED 9006', PLUGGED & ABANDONED.
 Did not rec load. (30 BLO, 178 BAW).

COUNTY	CHAVES	FIELD	Chaveroo	STATE	NM	OWWO
OPR	ATLANTIC-RICHFIELD COMPANY			MAP		
	5 Mona-Federal			CO-ORD		
	Sec. 17, T-8-S, R-13-E					
	1980' FNL, 1980' FEL of Sec.					
	Re-Spd 5-8-66			CLASS		
	Re-Cmp 5-31-66			OWWO		
		FORMATION	DATUM	FORMATION	DATUM	
LOGS & SX - TUBING						
13	3/8"	392'	350			
8	5/8"	3509'	835			
5	1/2"	9039'	400			
4	1/2"	4368'	250			
LOGS	EL	GR	RA	IND	HC	A
				TD 9040', PED 4331'		

IP San Andres Perfs 4234-86' Pmpd 23 BOPD + 4 BW. Pot. Based on 24 hr test.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 4450' TYPE
DATE

P.R. 5-12-66; OWWO
 PD 4450' - SA
 (Orig. P&A 4-11-65, OWT 9040')
 Elev. 4414' DF, Orig.
 5-19-66 AMEND OPERATOR: Formerly THE ATLANTIC REFG. CO.
 5-16-66 TD 9040', DO to 4331', swbg.
 Ran 4 1/2" casing @ 4368' w/250 ss.
 Drld out to 4331'
 Perf @ 4234', 4249', 4254', 4260', 4266',
 4272', 4275', 4286' w/1 SPI
 Ac (4234-86') 2000 gals.
 Swbd 16 BLO, 19 BNO, 30 BAW + 21 BW/12 hrs.
 Frac (4234-86') 25,000 gals oil + 21,000#
 sd. Spearheaded w/500 gals acid
 5-23-66 TD 9040', PED 4331', tstg on pump.
 Pmpd 18 BLO + 2 BAW/16 hrs (4234-86')
 5-31-66 TD 9040', PED 4331', tstg on pump.
 Pmpd 8 BNO, 7 BLO + 3 BW/16 hrs (4234-86')
 6-6-66 TD 9040', PED 4331', COMPLETE.