

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-15678

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR  
SUNDANCE OIL COMPANY

8. FARM OR LEASE NAME

Ingram Federal

3. ADDRESS OF OPERATOR  
Suite 510, 1776 Lincoln St., Denver, CO 80203

9. WELL NO.

1-Y

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

10. FIELD AND POOL, OR WILDCAT

Cato, San Andres

554' FNL, 554' FEL

Unit A

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 5, T.8S., R.31E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4263' GL

12. COUNTY OR PARISH

Chaves

13. STATE  
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL   
(Other)   
PULL OR ALTER CASING   
MULTIPLE COMPLETE   
ABANDON\*   
CHANGE PLANS

WATER SHUT-OFF   
FRACTURE TREATMENT   
SHOOTING OR ACIDIZING   
(Other) SET SURFACE CASING   
REPAIRING WELL   
ALTERING CASING   
ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 9/23/78. Drilled to 1505'. Ran 37 jts., 23#, 8 5/8" surface casing. Set at 1505'. Cemented with 300 sx Halliburton lite mixed with 1/4# flow seal, 8# Gilsonite, 2% CaCl followed by 200 sx Class C mixed w/2% CaCl. Circulated 50 sx. Plug down at 12:45 a.m. 9/25/78. Tested plug to 1000#, held okay.

RECEIVED  
SEP 29 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct  
SIGNED Richard O. Dimit TITLE Vice President, Production DATE 9/26/78

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE ACTING DISTRICT ENGINEER DATE SEP 29 1978  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
OCT 2 1950  
O.C.C.  
ARTEBIA, OFFICE