

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
SUNDANCE OIL COMPANY

3. ADDRESS OF OPERATOR  
#510, 1776 Lincoln St., Denver, CO 80203

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL, 1980' FWL, Unit C  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) SET PRODUCTION CASING	<input type="checkbox"/>		<input type="checkbox"/>

5. LEASE  
NM-15015-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Oakason "B" Federal

9. WELL NO.  
3

10. FIELD OR WILDCAT NAME  
Tom Tom, San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 33, T.7S., R.31E.

12. COUNTY OR PARISH  
Chaves

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4301' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to total depth of 4000'. Ran logs. Ran 101 jts. of 4½", 10.5# casing. Set at 3997' KB. Cemented with 300 sx 50/50 Pozmix mixed with 2% gel, ¼# Cello flakes, 8# salt. Plug down at 10 a.m. 4/19/79. Pressured up to 1300# for 15 minutes. Released rig 4/19/79. WOCU.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard O. Dimit TITLE VP, Production DATE April 23, 1979

(City, Sgd.) ALBERT R. STALL (This space for Federal or State office use) ACTING DISTRICT ENGINEER APR 25 1979  
APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 26 1979

O. C. C.  
ARTERIA, OFFICE

RECEIVED

APR 30 1979

OIL COMPANY OF CALIFORNIA  
LOS ANGELES