

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

USA NM 13418

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Amoco Federal

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Tom-Tom San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T-7-S, R-31-E

12. COUNTY OR PARISH 13. STATE

Chaves New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

MAR 19 1980

U.S. GEOLOGICAL SURVEY ARTESIA, NEW MEXICO

1. OIL WELL [X] GAS WELL [] OTHER []

2. NAME OF OPERATOR Flag-Redfern Oil Company

3. ADDRESS OF OPERATOR P.O. Box 2280 Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2173' FSL & 853' FEL Unit I Sec. 26, T-7-S, R-31-E

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4375 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF [] PULL OR ALTER CASING [] FRACTURE TREAT [] MULTIPLE COMPLETE [] SHOOT OR ACIDIZE [] ABANDON* [] REPAIR WELL [] CHANGE PLANS [] (Other) []

SUBSEQUENT REPORT OF:

WATER SHUT-OFF [] REPAIRING WELL [] FRACTURE TREATMENT [] ALTERING CASING [] SHOOTING OR ACIDIZING [] ABANDONMENT* [] (Other) Run 8-5/8" Surface Csg [X]

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 1626. Ran 39 jts 8-5/8" 24 lb/ft., J-55, ST&C casing to 1626'. Cemented w/600 sx Halliburton Light w/1/4# flocele, 8# salt, followed by 200 sx Cl "C" w/2% CaCl. Plug down at 1:00 a.m., 3-11-80. Circulated 70 sx to surface. Wait on cement 12 hrs and then tested casing to 1000 psi for 30 minutes.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineer DATE 3-18-80

(This space for Federal or State office use) [Signature] ACTING DISTRICT ENGINEER DATE MAR 19 1980

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: