

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPERF OR TO UNJACK UP OR TO REWORK EXISTING WELLS. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

GIL WELL GAS WELL OTHER

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th Street, Artesia, NM 88210

Location of Well

UNIT LETTER F 1980 FEET FROM THE North

THE West LINE, SECTION 36 T. 15S. R. 18E

15. Elevation (above a Water OF, FT, G. M., etc.)
4417.4' Cr.

1. Type of Lease Fee

2. State of Lease No. 2464

3. Field and Pool, or Without

4. Field Tomahawk SA

5. Locality

6. Survey

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

FORM REMEDIAL WORK
TEMPORARILY ABANDON
REPERF OR ALTER CASING
OTHER

PLUG AND ABANDON
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK
CONSERVATIVE REPERF OR ALTER CASING
CASING TEST AND CEMENT JOBS
OTHER production casing perforate and treat

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4298'. Ran 108 joints of 4 1/2" 9.5# ST&C J-57 (4300') of casing set at 4298'.
1-Regular guide shoe set at 4298'. 1-float collar set at 4258'. Ran 250 gallons Excello gel, and 2% KCl. Cemented with 300 sacks Class "G", 3% salt, .5% CF-9, 2% AF HD. Compressive strength of cement - 1000 psi in 12 hours. PD 12:45 pm 7-25-81. Bumped plug to 1250 psi released pressure and float held okay. WOC. WIH w/Steel Strip gun on wireline and perforated 4127-4179' w/11 .50" holes as follows: 4127, 29, 34, 41, 48, 53, 69, 74, 77 & 79'. Acidized with 1500 gallons 20% HCl acid and 30 ball sealers. WIH w/Steel Strip gun on wireline and perforated 4058-4104' w/12 .50" holes as follows: 4058, 60, 63 1/2, 68, 73 1/2, 75 1/2, 79 1/2, 83, 86, 88, 91 1/2 & 94'. Acidized perforations with 1500 gallons 20% HCl acid and 30 ball sealers. Install pumping equipment.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED BY: [Signature] TITLE: Engineering Secretary DATE: 8-24-81

APPROVED BY: [Signature] TITLE: DATE:

CONDITIONS OF APPROVAL, IF ANY: