

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Getty Oil Co.	8. Farm or Lease Name B. D. Taylor
3. Address of Operator P. O. Box 728, Hobb, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER P 660 FEET FROM THE south LINE AND 660 FEET FROM East 28 15-S 31-E THE LINE, SECTION TOWNSHIP RANGE NMPM.	10. Field and Pool, or Wildcat Undesignated Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 4393' (GR)	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TOTAL DEPTH 13,540'
13 3/8" OD 54.5# K-55 CSG SET @ 405'
8 5/8" OD 32# J-55 CSG SET @ 4086'

- Spot 50 sx cement plug 13,399-13,210' (PBSD 13,210').
- Ran 12,397' (300 JTS.) 5 1/2" OD 17# S-95 & N-80 Csg & Set @ 12,415'.
- Cemented 1st stage W/800 sx LW Cement containing 1/4# Flocele per sack followed W/200 sx 50/50 POZMIX/class H Cement containing 1/4# Flocele & .8% Halad-9 per sack.
- With DV Tool open @ 9500' Cemented 2nd stage W/1500 sx LW Cement containing 1/4# Flocele per sack. Cement circulated. Job complete 3:30 AM, 12-22-84. WOC in excess of 18 hrs.
- Tested 5 1/2" Csg to 1000# for 30 minutes, 6:00-6:30 AM, 1-4-85. Tested OK. Job complete 6:30 AM, 1-4-85.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.A. Baker II TITLE Dist. Opr's. Mgr. DATE 1-14-85

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

JAN 18 1985

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 17 1985

HOUSTON OFFICE