## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well,

	Indicate Nature of H	Report by Checkin	ng Below	7	
EPORT ON BEGINNING PRILLING OPERATIONS	REPORT ON RE OF CASING SHU		x	REPORT ON REPAIRING WEI	.L
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOPERATION	COMPLETION		REPORT ON (Other)	
	<b>Ap</b> r	:11 14-55			Midland, Texas
Following is a report on the work	done and the results obtain	ned under the head	ling note	d above at the	
The Superior O	il Company			State "333	<b>11</b>
Western Drilli (Contractor	ng Company	, Well No. 1-3	33	in the <b>SW</b> 1/4 <b>8</b>	W 1/4 of Sec. 19
13-8 , R 32-E , NMPM.,	Caprock	Pool,		Les	County,
he Dates of this work were as folows:					
otice of intention to do the work (was)	( submitted on For	rm <b>C-101</b>	X	arch 29	
d approval of the proposed plan (was)			(Cr	oss out incorrect words)	
	(was not) obtained.				
Drilled 8-3/4" hele	to 3073'. Ran & c	emented 7"	20#, J	-55, R-2, ST&C	csg to 3073' w/
DETAII	to 3073'. Ran & c llam 4-11-55. Fina 1000# for 30 mins, shut-off on 7" cas o dead in 4 mins.	emented 7" and 1 Pressure 1 OK, cleaned ing w/4 jet Rec 5' of di	20#, J 1300#. 1 out shots	cement inside in 7" csg @30	7" casing to 307
Drilled 8-3/4" hele 150 sax Long Horn & Tested 7" casing w/ Took DST for Water- for 15 mins, VWRA t Cored 6-1/8" hole for	to 3073'. Ran & c llam 4-11-55. Fina 1000# for 30 mins, shut-off on 7" cas o dead in 4 mins.	emented 7" and 1 Pressure 1 OK, cleaned ing w/4 jet Rec 5' of di	20#, J 1300#. 1 out shots rlg mu	cement inside in 7" csg @30 d, FBHP Of, te	7" casing to 307, 70-71. Tool epen st satisfactory.
Drilled 8-3/4" hele 150 sax Long Horn & Tested 7" casing w/ Took DET for Water- for 15 mins, VWRA t Cored 6-1/8" hele for	to 3073'. Ran & c llam 4-11-55. Fina 1000# for 30 mins, shut-off on 7" cas o dead in 4 mins.	omented 7" all Pressure :  OK, cleaner ing w/4 jet Rec 5' of di TD	20#, J 1300#. 1 out shots rlg mu	cement inside in 7" csg e30 d, FBHP Of, te	7" casing to 307, 70-71. Tool epen st satisfactory.
Drilled 8-3/4" hele 150 sax Long Horn & Tested 7" casing w/ Took DET for Water- for 15 mins, VWBA t  Cored 6-1/8" hele for  Vitnessed by J. E. Fergusen (Name)  pproved:	to 3073'. Ran & c llam 4-11-55. Fina 1000# for 30 mins, shut-off on 7" cas o dead in 4 mins. rom 3073' to 3084'	OK, cleaned ing w/4 jet Rec 5' of di TD  uperior Oil (Company)	20#, J 1300#. 1 out shots rlg mu	cement inside in 7" csg e30 d, FBHP Of, te	7" casing to 307. 70-71. Tool open st satisfactory.  Tool Pusher
Drilled 8-3/4" hele 150 sax Long Horn & Tested 7" casing w/ Took DST for Water- for 15 mins, VWRA t Cored 6-1/8" hele for	to 3073'. Ran & c llam 4-11-55. Fina 1000# for 30 mins, shut-off on 7" cas o dead in 4 mins. rom 3073' to 3084'	OK, cleaned ing w/4 jet Rec 5' of di TD  uperior Oil (Company)	Compa.  Compa.  Ty that the my known in the compa.	cement inside in 7" csg e30 d, FBHP Of, te	Tool Pusher  Tool Pusher  Tool Structure  (Lemer Strick)
Drilled 8-3/4" hele 150 sax Long Horn & Tested 7" casing w/ Took DET for Water- for 15 mins, VWRA t Cored 6-1/8" hele for Witnessed by J. E. Fergusen (Name)	to 3073'. Ran & c llam 4-11-55. Fina 1000# for 30 mins, shut-off on 7" cas o dead in 4 mins. rom 3073' to 3084'	OK, cleaned of the control of the co	Compa.  Compa.  Compa.  Compa.  The	cement inside in 7" csg €30 d, FBHP Of, te	Tool Pusher  Tool Pusher  Tool Structure  (Lemer Strick)