


OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO



Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

August 4, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Amerada Petroleum Corporation State of TX Well No. 1 in the

Company or Operator

Lease

C/SR/L W/L of Sec. 23, T. 12-S, R. 33-E, N. M. P. M.,

Hightower Field Lea County.

The dates of this work were as follows: July 27 & 28, 1950

Notice of intention to do the work was submitted on Form C-102 on July 26, 1950

and approval of the proposed plan was obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11,185' - Total Depth - Lima. Run Schlumberger's Electrical, Gamma Ray and Dipmeter Surveys. No. 1 plug from 11185' to 11056' with 35 sacks Lane Star Reg. cement, No. 2 plug from 8753' to 8624' with 35 sacks Lane Star Reg. cement, No. 3 plug from 3950' to 3841' with 35 sacks Lane Star Reg. cement, No. 4 plug from 1550' to 1470' with 25 sacks of Lane Star Reg. cement - Heavy mud between all plugs. Shot off 8-5/8" casing at 1248' with 4 quarts of liquid nitre & pulled 1236' of 8-5/8" O.D. casing. Plugged 11" hole from 315' to 272', inside of 13-3/8" O.D. casing w/35 sacks Reg. cement. Plugged top of 13-3/8" casing w/10 sacks Reg. cement.

Witnessed by E. V. Stephenson Amerada Petroleum Corporation Peruman (Over)

Name

Company

Title

Subscribed and sworn before me this.....

I hereby swear or affirm that the information given above is true and correct.

4th day of August, 19.....

Name

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation Company or Operator

My commission expires 10-24-53

Address Drawer B, Monument, New Mexico

Remarks:

APPROVED

Date AUG - 8 1950

Ray Zuehlke
Name
Oil & Gas Inspector
Title

Comment. Set a piece of 4" Line Pipe, cemented in center of the surface casing, 5' above surface of ground. Well plugged & abandoned at 11:30 A.M., 7-28-50.