

**DUPLICATE**

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**

FEB 20 1953

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<b>X</b>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

**February 18, 1953**  
(Date)

**Tatum, New Mexico**  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

**Amerada Petroleum Corporation**  
(Company or Operator)

**Junious Talk**

(Lease)

**Noble Drilling Corporation**  
(Contractor)

Well No. **1** in the **6/ SE/ 1/4 SW/ 1/4** of Sec. **22**

T. **13-S, R. 33-E**, NMPM., **Lazy "J"** Pool, **Lea** County.

The Dates of this work were as follows: **February 17, 1953**

Notice of intention to do the work (was) ~~shown~~ submitted on Form C-102 on **February 17**, 19**53**,  
(Cross out incorrect words)

and approval of the proposed plan ~~was~~ (was not) obtained.

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

**10,495' T.D. - Filled hole with heavy mud from 10,495' to 9307' - spotted cement plug from 9307' to 9194' with 35 sacks regular cement. Filled hole with heavy mud from 9194' to 3983' and spotted cement plug from 3983' to 3871' with 35 sacks regular cement. Ran McCullough jet casing cutter and shot 8-5/8" OD casing off at 567'. Pulled 552' of 8-5/8" OD casing. Filled hole with heavy mud from 3871' to 12' from surface and spotted 10 sacks regular cement in top of 13-3/8" casing. Set piece of 4" line pipe extending 5' above ground level in cement to serve as marker - Well plugged and abandoned 2/17/53.**

Witnessed by **R. J. Brakey** **Amerada Petroleum Corporation** **Farm Boss**  
(Name) (Company) (Title)

Approved: **OIL CONSERVATION COMMISSION**

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: **[Signature]**

Position: **Assistant District Superintendent**

Representing: **Amerada Petroleum Corporation**

Address: **Roswell Star Route Tatum, New Mexico**

**Roy Yunker**  
(Name)  
**Inspector**  
(Title)  
**MAY 18 1953**  
(Date)

