NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Chec	king Below		* .
EPORT ON BEGINNING PRILLING OPERATIONS	REPORT ON RESULT OF TES OF CASING SHUT-OFF		T ON RING WELL	
EPORT ON RESULT F PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPOR (Other)		
	April 6, 1953	Tatum,	New Mexico	lace)
	done and the results obtained under the h	eading noted above at	the	
Amerada Petroleum Gor; (Company or Ope	***************************************			
	tion Well No.		ase) I/ 1/4 IIV 1/4 (of Sec.
•	Asy njn Po	ol. Los		Count
	April 5, 1953			
to Dates of this work were as follows:		***************************************	***************************************	••••••••••••••••
tice of intention to do the work				
thee of memors to do the work	(was not) submitted on Form C-102 on	(Marana and Inc.)		, 19
d approval of the proposed plan (DETAII) 7760 Total Depth.	Lime. Finished drilling	RESULTS OBTAIN	ed 5:00 am. 4/2/	53.
9760' Total Depth. Ran Schlumbe set @ 9675' @ 3:13 PM, 4 — top of cem After WCC fo	(was not) obtained. LED ACCOUNT OF WORK DONE AND	RESULTS OBTAIN 2-7/2" hele 6 ; 286 joints of cement. Pumped 1500# Han tem at 7565; of g w/ 1000# for to 9660; — To	5:00 AM, 4/2/ 5-2" OD cas pareture sur 50.9% Fill. 1/2 hear - 1	53. ing g: vey no sing
9760' Total Depth. Ran Schlumbe set @ 9675' @ 3:13 PM, 4 - top of cen After WOC for pressure dro with 1000f for	Lime. Pinished drilling arger surveys. Ran a total or and comented with 600 sacks /3/53. Max. Pump Pressure — ent outside of 5-2" OD easing 24 hours tested 5-2" casing p. Drilled coment from 9590 or 1/2 hour — no pressure dr	RESULTS OBTAIN 2-7/8" hele 6 9 288 joints of cement. Pumped 1500# Han tem is at 7565! of is w/ 1000# for to 9660! — To pp. Continued	ED 1:00 AM, 4/2/ 2:5-2" OD cas 1 plug to 959 perature sur 50.9% Fill. 1/2 hear - 1 ested 5-2" ca with complet:	53. ing g: vey no sing
9760' Total Depth. Ran Schlumbe set e 9675' e 3:13 PM, 4 - top of cen After WCC fo pressure dro with 1000f f operations.	Lime. Pinished drilling arger surveys. Ran a total or and comented with 600 sacks /3/53. Max. Pump Pressure — ent outside of 5-2" CD easing 24 hours tested 5-2" casing. Drilled coment from 9590	RESULTS OBTAIN 2-7/8" hele 6 9 288 joints of cement. Pumped 1500# Han tem is at 7565! of is w/ 1000# for to 9660! — To pp. Continued	5:00 AM, 4/2/ 5-2" OD cas pareture sur 50.9% Fill. 1/2 hear - 1	53. ing g: vey no sing
7760' Total Depth. Ran Schlumbe set 6 9675' 6 3:13 PM, 4 - top of cem After WCC for pressure drowith 1000f for operations. The set of the pressure drowith 1000f for operations.	Lime. Pinished drilling reger surveys. Ran a total or and comented with 600 sacks /3/53. Max. Pump Pressure - ent outside of J-2" CD easier 24 hours tested 5-2" casier. Drilled coment from 9590 or 1/2 hour - no pressure dr	RESULTS OBTAIN 2-7/8" hele 6 9 288 joints of cement. Pumped 1500# Han tem is at 7565! of is w/ 1000# for to 9660! — To pp. Continued	Farm Boss	53. ing g: vey no sing
7760' Total Depth. Ran Schlumbe set e 9675' e 3:13 PM, 4 - top of com After WCC for pressure drowith 1900f for operations. The second	Lime. Pinished drilling greer surveys. Ran a total or and comented with 600 sacks /3/53. Max. Pump Pressure — ent cutside of 5-2" CD easing 24 hours tested 5-2" casing. Drilled coment from 9590 or 1/2 hour — no pressure drive dr	RESULTS OBTAIN 2-7/8" hele 6 ; 288 joints of coment. Pumped 1500# Han ten g at 7565; of g w/ 1000# for to 9660; — To 96	Farm Boss	53. ing g: vey ne sing ion
7760' Total Depth. Ran Schlumbe set e 9675' e 3:13 PM, 4 - top of com After WCC for pressure drowith 1900f for operations. The second	Lime. Pinished drilling greer surveys. Ran a total or and comented with 600 sacks /3/53. Max. Pump Pressure — ent cutside of 5-2" CD easing 24 hours tested 5-2" casing. Drilled coment from 9590 or 1/2 hour — no pressure drive dr	RESULTS OBTAIN 2-7/2" hele 6 ; 286 joints of coment. Pumped 1500# Han ten ten ten to 9660! - To 96	Farm Boss (Title)	53. ing 3: vey ne sing ion
7760' Total Depth. Ran Schlumbe set e 9675' e 3:13 PM, 4 - top of com After WCC for pressure drowith 1900f for operations. The second	Lime. Pinished drilling reger surveys. Ran a total or and commented with 600 sacks /3/53. Max. Pump Pressure - ent cutside of 5-2" CD easier 24 hours tested 5-2" casis p. Drilled coment from 9590 or 1/2 hour - no pressure drive in the best of the	RESULTS OBTAIN 2-7/2" hele 6 ; 286 joints of coment. Pumped 1500# Han ten ten ten to 9660! - To 96	Farm Boss (Title)	53. ing g: vey ne sing ion

they guilding in

and the second of the second o