## NE vv MEXICO OIL CONSERVATION COMINISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

OCI 29 1952

days after the work specified is company
s shungff property for the light in 1950.

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days pleted. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shresult of well repair, and other important operations, even though the work was witnessed by an agent of instructions in the Rules and Regulations of the Commission.

instructions in the Rules and Regulations	of the Commission.			MOBDS	
	Indicate Nature of	f Report by Checki	ing Below		
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON I	RESULT OF TEST HUT-OFF	B	RT ON RING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON I	RECOMPLETION	REPOR (Other		
•	Oct	tober 27, 195	2	Hebbs, New Me	exico
Following is a report on the work	done and the results obt	tained under tne hea	ding noted above a	t the	
Gulf Oil Corporation (Company or Operator)		Lea State BS (Lease)			······································
Southeastern Drilling (Contractor)	empany	, Well No. 1	in the M	1/4 NE 1/4 of	f Sec <b>27</b>
г. <b>13-8</b> , r. <b>33-8</b> , nmpm., <b>U</b>	ndesignated	Pool	i,	l <b>a</b>	Count
The Dates of this work were as follows:	October 22 -	- 24, 1952			
otice of intention to do the work	(was not) submitted on	Form C-102 on	(Cross out inco	rrect words)	19
	(was not) obtained.				
nd approval of the proposed plan DETAIL  Ran 7 joints 2821 o	ED ACCOUNT OF WO	# R-3 casing	. Set and cen	ented at 303'	
nd approval of the proposed plan <b>DETAIL</b>	ED ACCOUNT OF WO f 12-3/4" OD 50% El Toro cement.  24 hours tested no drop in press below casing sh	# R-3 casing Plug at 280  12-3/4" casisure. Drilled	. Set and cen '. Maximum pr  ng w/800# pre cement plug	essure 200#. essure for 30 from 280' to	r•
DETAIL  Ran 7 joints 282' o  w/400 sacks regular  cament circulated.  After waiting over  minutes. There was  303', tested cament	ED ACCOUNT OF WO f 12-3/4" OD 50% El. Tore cement.  24 hours tested ne drop in press below casing shours.	R-3 casing Plug at 280 12-3/4" casing sure. Drilled noe w/400# pro	. Set and cent. Maximum prong w/800# pro- cement plugessure for 30	essure 200#. essure for 30 from 280' te minutes. Then	
DETAIL Ran 7 joints 282' o w/400 sacks regular cament circulated.  After waiting over minutes. There was 303', tested cement was no drop in pres	ED ACCOUNT OF WO f 12-3/4" OD 50% El Tore cement.  24 hours tested no drop in press below casing shaure.  27. Yarbrough, St	R-3 casing Plug at 280 12-3/4" casing sure. Drilled noe w/400# pro	. Set and cent. Maximum prong w/800# pro- cement plugessure for 30	essure 200#. essure for 30 from 280' te minutes. Then	
DETAIL  Ran 7 joints 282' o w/400 sacks regular coment circulated.  After waiting over minutes. There was 303', tested coment was no drop in pres  After approval of M	ED ACCOUNT OF WO f 12-3/4" OD 50% El Tore cement.  24 hours tested no drop in press below casing shaure.  27. Yarbrough, St	R-3 casing Plug at 280 12-3/4" casing sure. Drilled noe w/400# pro	. Set and cent. Maximum prong w/800# pro- cement plugessure for 30	essure 200#. essure for 30 from 280' te minutes. Then	
DETAIL  Ran 7 joints 282' o w/400 sacks regular coment circulated.  After waiting over minutes. There was 303', tested coment was no drop in pres  After approval of M were made to drill	ED ACCOUNT OF WO f 12-3/4" OD 50% El Toro cement.  24 hours tested ne drop in press below casing shours.  Tr. Yarbrough, Stahead.	# R-3 casing Plug at 280  12-3/4" casing Rure. Drilled Rure w/400# pro	. Set and cen '. Maximum pr  ng w/800# pre cement plug essure for 30  Gas Inspector	essure 200#. essure for 30 from 280' to minutes. Then	•
DETAIL  Ran 7 joints 282' o  w/400 sacks regular  cement circulated.  After waiting over  minutes. There was  303', tested cement  was no drop in pres  After approval of M	ED ACCOUNT OF WO f 12-3/4" OD 50% El Toro cement.  24 hours tested ne drop in press below casing shours.  Tr. Yarbrough, Stahead.	R-3 casing Plug at 280 12-3/4" casing sure. Drilled noe w/400# pro	. Set and cen '. Maximum pr  ng w/800# pre cement plug essure for 30  Gas Inspector	essure 200#. essure for 30 from 280' te minutes. Then	•
DETAIL  Ran 7 joints 282' o w/400 sacks regular cement circulated.  After waiting over minutes. There was 303', tested cement was no drop in pres  After approval of M were made to drill  Witnessed by	ED ACCOUNT OF WO f 12-3/4" OD 50% El Toro coment.  24 hours tested no drop in press below casing sheare.  3. Yarbrough, Stahead.  Gulf.	R-3 casing Plug at 280  12-3/4" casing Bure. Drilled Hoe w/400# pro tate Oil and ( Company)  I hereby cere	. Set and cent. Maximum prong w/800# prong w/800# prong cement plug essure for 30 Gas Inspector	essure 200#. essure for 30 from 280' to minutes. Then	
DETAIL  Ran 7 joints 282' o w/400 sacks regular coment circulated.  After waiting over minutes. There was 303', tested coment was no drop in pres  After approval of M were made to drill  Witnessed by	ED ACCOUNT OF WO f 12-3/4" OD 50% El Toro coment.  24 hours tested no drop in press below casing sheare.  3. Yarbrough, Stahead.  Gulf.	R-3 casing Plug at 280  12-3/4" casing Bure. Drilled noe w/400# pro tate Oil and ( Company)  I hereby cert to the best of	Maximum programming w/800# programming to the same for 30 gramming the	essure 200#.  essure for 30 from 280' to minutes. Then  rilling Forem (Title)  tion given above is tru	
DETAIL  Ran 7 joints 282' o w/400 sacks regular coment circulated.  After waiting over minutes. There was 303', tested coment was no drop in pres  After approval of M were made to drill  Witnessed by	ED ACCOUNT OF WO f 12-3/4" OD 50% El Toro coment.  24 hours tested no drop in press below casing sheare.  3. Yarbrough, Stahead.  Gulf.	R-3 casing Plug at 280  12-3/4" casing Bure. Drilled noe w/400# pro tate Oil and ( Company)  I hereby cert to the best of Name	Set and con Maximum pr  I Maxi	essure 200%.  essure for 30 from 280' to minutes. Then  rilling Forem  (Title)  tion given above is tru	

1- (272) 322 (2)

•