

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-105
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-10137

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- P & A
2. Name of Operator Atlantic Richfield Company
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201
4. Location of Well UNIT LETTER A 330 FEET FROM THE North LINE AND 330 FEET FROM East THE 33 LINE, SECTION 13-S TOWNSHIP 33-E RANGE 33-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4234' GR

7. Unit Agreement Name
8. Farm or Lease Name State 245
9. Well No. 3
10. Field and Pool, or Wildcat Lazy J.-Penn.
12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has been plugged & abandoned in the following manner:

Set 5½" 17# CIBP @ 9530' WLM. Capped w/2 sx cement. Shot off 5½" casing @ 4020', pulled 111 jts (4003') of 5½" casing. Spotted 30 sk cement plug 4021-3917'. Placed 20 sk cement plug in top of 8-5/8" casing. 9# salt gel mud was used to spot all plugs. 13-3/8" & 8-5/8" casing remain intact. Installed dry hole marker. **Well P & A 2/13/71.**

Your office will be notified when location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>W.D. Litcher</i></u>	TITLE <u>Dist. Drlg. Supervisor</u>	DATE <u>2/17/71</u>
APPROVED BY <u><i>Nathan E. Olegg</i></u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>JUN 19 1972</u>

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 10 1971

OIL CONSERVATION COMM.
HOBBES, N. M.