

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

RECEIVED

OCT - 2 1950

OIL CONSERVATION COMMISSION
HOBBS-OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 28, 1950

Moorhead, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Amerada Petroleum Corporation State S "A" Well No. 1 in the
Company or Operator Lease
C/M/4 NE/4 of Sec. 35, T. 14-S, R. 33-E, N. M. P. M.,
Wildest Field Lee County.

The dates of this work were as follows: September 10th to 28th, Incl., 1950Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on September 10, 19 50and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran water locator surveys, plugged back w/plastic from 10020' to 9987', perforated 5-1/2" casing from 9976' to 9987' w/4 S.P.F. In 25 hrs. swabbed .62 bbl. oil & 76.97 bbls. water. Acidised w/500 Gal. Dowell mud acid & in 35 hrs. swabbed 454.79 bbls. water. Squeezed cemented perforation from 9976' to 9987' w/150 sacks cement. 50 sacks in formation, 100 sacks reversed out. Drilled cement to 9985' & perforated 5-1/2" casing from 9967' to 9985' w/4 S.P.F. Swabbed 8.12 bbls. water in 13 hrs. Drilled cement from 9985' to 10005' & perforated 5-1/2" casing from 9998' to 10005' w/4 S.P.F. In 24-1/2 hrs. swabbed 10.96 bbls. oil, 55.12 bbls. water. Acidised w/500 Gal. Dowell 15% L.T. acid. Swabbed & flowed 221.66 bbls. oil & 72.97 bbls. BS & water in 71-1/2 hrs. (Cont'd. to reverse side) E. E. Shirley Amerada Petroleum Corporation Farm Boss

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn before me this.....

28th day of September, 19 50

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Dan ToppPosition Assistant District SuperintendentRepresenting Amerada Petroleum Corporation
Company or OperatorMy commission expires 10-24-53Address Drawer D, Moorhead, New Mexico

Remarks:

APPROVED
OCT - 2 1950

Date _____

Neg. Yachroff
Name _____
Oil & Gas Inspector
Title _____

(Continued from reverse side)

Acidised with 2000 Gal. Dowell 15% L.T. acid and in 32-1/2 hours
swabbed 28.11 barrels of oil and 80.81 barrels of water. Notice
of Intention to Plug Well is being submitted this date.