

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANITARY	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

VERBAL PERMISSION TO P&A FROM
MR. JERRY SEXTON APRIL 26, 1983

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Name of Lease Name Heidel
9. Well No. 1 SWD
10. Field and Pool, or Unit King (Devonian)
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR NOTICES TO ABANDON OR TO RE-ENTER A WELL OR TO A DIFFERENT RESERVOIR.
(SEE INSTRUCTIONS FOR PERMIT TO DRILL OR CEMENT FOR SUCH PURPOSES.)

1. Name of Operator
UNION TEXAS PETROLEUM CORP.

2. Address of Operator
1400 Wilco Bldg., Midland, TX 79701

3. Location of Well
UNIT LETTER J 1650 FEET FROM THE South LINE AND 2310 FEET FROM
THE East LINE, SECTION 1 TOWNSHIP 14-S RANGE 37-E NMPM.

11. Elevation (Show whether DF, RT, GR, etc.)
3827' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Re-entered well and drilled out cement plug at surface (35').
2. Drilled 8 3/4" hole to 1787' below 13 3/8" csg. and outside 9 5/8" csg. stub @ 1473'.
3. Ran caliper survey and verified new hole outside of 9 5/8" csg. Logged from 1530'-1586'.
4. Spotted 80 sx. cement plug @ 1420'-1525', 247'-355' and 15 sx. plug @ surface. (Cement Class "C" w/2% CaCl₂).
5. Welded steel plate on 13 3/8" surface casing and set marker.
6. Covered cellar and working pits, cleaned and levelled location. (Well annulus was filled w/10#/gal. mud laden fluid containing 25# of gel/bbl).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>William D. Higgins</u>	TITLE <u>Prod. Services Supr.</u>	DATE <u>May 11, 1983</u>
APPROVED BY <u>Jack Griffin</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>MAY 12 1983</u>

RECEIVED
MAY 12 1983
O.C.D.
HOBBS OFFICE

Union Texas Petroleum
Heidel No. 1.

Condition after re-entry.

13 3/8" @ 305

95/8' Stub @ 1493

8³/₄ inch wide 1³/₄ inch
1787.

9 5/8" CSg @ #661 w/ 25 ex plug.
#642 - #692

8 3/4" OK

25 ex. plug 9470'

25 exp lug @ 12,885'

San Andres Por.
5600' - 6100'

Glorieta Pk.
6100' - 6700'

RECEIVED
MAY 12 1983
O.C.D.
MOBBS OFFICE

Condition after Union Texas Petroleum
Heidel No. 1.
Plugging.

Steel Plate
15 ex cmt. Plug at Surface

80 ex. Cmt. Plug
247' - 355'

13 3/8" @ 305

80 ex. Cmt. plug
1420 - 1525

9 5/8" Stub @ 1493

9 5/8" CSG @ 4661 w/ 25 ex plug.
4642 - 4692

San Andres Por.
5600' - 6100'

8 3/4" OH

Glorieta Por.
6100' - 6700'

25 ex. plug 7470'

25 ex plug @ 12,825'

