

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)10-31-62
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Cities Service Production Company Miller B Well No. 1 in I
(Company or Operator) Lease (Unit)
NE 1/4 SE 1/4 of Sec. 18, T. 12-S., R. 38-E, NMPM, Gladiola-Wolfcamp Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was originally drilled to TD 12,026' in the devonian formation PBTD 12,023'. It was re-completed in the Wolfcamp formation @ PBTD 9558' w/perforations from 9522'-9532'; 9542'-9555'.

This well is now non-commercial and it is proposed to P & A in the following manner:
(1) load hole w/mud ladden fluid; (2) set 25 sacks cement plug from 9558'-9338' (to cover open perforations); (3) set 35 sacks cement plug 135' below and 55' above stub where 5 1/2" casing will be cut off; (4) set 35 sacks cement plug from 4449' to 4554' (to cover base of 8 5/8" casing set @ 4499'); (5) set 10 sacks cement plug from 20'-surface w/4" marker extending 4' above ground level to designate P & A location; (6) clean location of all debris, fill cellar and level pits in a workman-like manner.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Cities Service Production Company

Company or Operator

By.....

Position..... Dist. Supt.

Send Communications regarding well to:

Name..... G. M. Geyer

Address..... Box 97, Hobbs, New Mexico