

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	XX	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico,
(Place)May 21, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sinclair Oil & Gas Company Richardson Well No. 1-5 in N (Unit)
(Company or Operator) LeaseSW 1/4 SW 1/4 of Sec. 5, T. 14S, R. 36E, NMPM, Wildest Pool
(40-acre Subdivision)

Leon County.

Per verbal w/ Mr. Engbrecht 2/21/63 by OOG

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 13494 - Dry Hole - Set 5 1/2" OD Casing @ 13494 - Cement behind 5 1/2" Casing @ 10375'
 Miss. Perforated 13349-65 & 71-83 w/ 5/8" holes & Treated - Tested dry
 Set Cast Iron Bridge Plug @ 13252 w/ 1 Sk. Cement - Top plug @ 13244
 Atoka Perforated 12867-79 w/ 2 1/2" holes & Treated - Tested dry
 Set Cast Iron Bridge Plug @ 12810 w/ 1 Sk. Cement - Top plug @ 12802
 Atoka Perforated 12317-23 w/ 12 holes & Treated - Tested dry
 Propose to Set Cast Iron Bridge Plug @ 11428 w/ 1 Sk. Cement - Top Plug 11420
 Cut 5 1/2" Casing off @ 10375 - Set 25 Sk. cement plug in top of 5 1/2" stub - Fill hole w/ Hy. Mud.
 Set 25 Sk. plug @ 9800' Set Cast Iron Bridge Plug @ 12240 w/ 1 Sk. cement TP 12232'.
 " 25 " " @ 7500' Canyon - Perf. 11478-86 w/ 1 1/2" holes & Treated - Tested dry.
 " 25 " " @ 6100'
 " 25 " " in base of 8 5/8" OD Casing set @ 4627' - Cut 8 5/8" off @ Approx 2800'
 Set 25 " " in 8 5/8" stub - Base Salt 2875' - 25 Sk. cement plug @ 2250' (Top Salt)
 " 25 " " @ 378' Base 13 3/8" OD Casing - Keep hole fill heavy mud -
 Set 4" "Regulation Marker" Extend 4' above surface level - in 10 Sk. cement in top
 of 13 3/8" OD Casing & Cemented Bottom of Casing - Plugged & Abandon

Approved....., 19.....
Except as follows:

Sinclair Oil & Gas Company

By.....

Position Dist. Supt.

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Name W. F. Burns.

Title.....

Address 520 E. Broadway, Hobbs, N.M.

