

	O. D.	I. D.	LENGTH	DEPTH
Drill Pipe or Tubing	6"	3"	1.50'	13326.44'
Reversing Sub				
Water Cushion Valve				
Drill Pipe	4½"	3.826"	12805'	
Drill Collars	6.25"	2.25"	521'	
Handling Sub & Choke Assembly				
Dual CIP Valve				
Dual CIP Sampler				
Hydro-Spring Tester				
Multiple CIP Sampler	5"	.75"	8.39'	13476.44'
Extension Joint	5"	.87"	12.39'	
AP Running Case	5"	3.06"	4.14'	13498.10'
Hydraulic Jar	5.03"	1.75"	5'	
VR Safety Joint	5"	1"	2.78'	
Pressure Equalizing Crossover				
Packer Assembly	5.06"	1.56"	4.07'	13509.20'
Distributor				
Packer Assembly	5.06"	1.53"	4.07'	13514.13'
Flush Joint Anchor				
Pressure Equalizing Tube X over	5"	2.20"	.80'	
Blanked-Off B.T. Running Case				
Drill Collars	6.25"	2.18"	67.20'	
Anchor Pipe Safety Joint X over	5"	2.20"	.80'	
Packer Assembly				
Distributor				
Packer Assembly				
Anchor Pipe Safety Joint	5.75"	1.50"	4'	
Side Wall Anchor				
Drill Collars				
Flush Joint Anchor	5.75"	2.87"	30'	
Blanked-Off B.T. Running Case	5.75"	2.50"	6'	13615.72'
Total Depth				13620'