

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SEP 27

5a. Indicate Type of Lease	State <u>NM</u> '67	Fee <input checked="" type="checkbox"/>
----------------------------	---------------------	---

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- DRY HOLE	7. Unit Agreement Name
2. Name of Operator MONSANTO COMPANY	8. Farm or Lease Name HANNAH
3. Address of Operator 101 N. Marienfeld, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>14-S</u> RANGE <u>36-E</u> NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3982' DF	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER _____

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER _____

ALTERING CASING ☒
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

This well was drilled to a total depth of 11,325' and found to be non-commercially productive of oil or gas. 11-3/4" casing had been set at 400' and cemented to surface and 8-5/8" casing at 4650' and cemented to 1500'.

On 8-30-67 verbal approval to plug and abandon was obtained from Mr. E. F. Engbrecht by M. D. Lambert.

On 8-30-67 filled hole with mud laden fluid between cement plugs. Placed cement plugs as follows: 25 sx 11,325-11,234', 25 sx 10,000-9919', 25 sx 5140-6059', 50 sx 4700-4538'. Shot off 8-5/8" casing at 1143' and pulled, leaving 3570' of 24# & 32# casing in hole. Placed cement plugs as follows: 20 sx 1177-1120', 50 sx 430-348', 10 sx at surface. Set 4" diameter steel marker in concrete with well name, number, and location marked thereon.

Plugging completed 7:30 p.m. 8-31-67.

You will be notified when pits have been filled and location has been cleaned up and ready for your inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. W. Wood A. W. Wood TITLE Dist. Prod. Supt. DATE Sept. 26, 1967

APPROVED BY John W. Runyan TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: