

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

MINERAL CONSERVATION DIV. J.C.
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-2109	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Harper Oil Company		Seay
3. Address of Operator		9. Well No.
904 Hightower Building Oklahoma City, Oklahoma 73102		1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>East</u> LINE AND <u>660</u> FEET FROM		Hightower
THE <u>South</u> LINE, SECTION <u>30</u> TOWNSHIP <u>12S</u> RANGE <u>34E</u> N.M.P.M.		Lower Penn
11. Elevation (Show whether DF, RT, GR, etc.)		12. County
4201.8 GL		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded at 11:00 A.M. 5-20-80.
- Drilled 17½" hole to 360'. Dev: 3/4° at 245', 3/4° at 360'.
- Ran 9 jts. 13 5/8" 48# H-40 ST&C casing. Set at 360' KB. Cemented with 400 sacks Class C w/2% CaCl. PD @ 9:15 P.M. 8-20-80. Circulated 63 sacks good cement to surface.
- Wait on cement 24 hrs. Nipple up B.O.P. stack and choke manifold. Pressure tested to 750# 45 mins. held okay. Drilled float collar and 40' of good cement.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Jerry Sexton</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>May 28, 1980</u>
APPROVED BY <u>Dist. L. Supv.</u>	TITLE _____	DATE <u>JUN 2 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		