

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

3a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
3. State Oil & Gas Lease No.	
E-7169	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry		7. Unit Agreement Name
2. Name of Operator CELERON OIL AND GAS COMPANY		8. Farm or Lease Name State
3. Address of Operator P.O. Box 52088 Lafayette, La. 70505		9. Well No. 1
4. Location of Well UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 33 TOWNSHIP 13S RANGE 38E NMPM.		10. Field and Pool, or Wildcat WC
15. Elevation (Show whether DF, RT, GR, etc.) 3818 GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER Cmt & test casing <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

31 Oct. 82 Cemented 535' of 13-3/8" casing in 17 1/2" hole with 450 sx class "C" with 2% CaCl<sub>2</sub>. Bumped plug with 200 psi, floats did hold. Held 200 psi on casing for 75 minutes, no drop. Circ approx. 13 bbls. W.O.C. 21 3/4 hrs, test to 1000#, no leaks.

7 Nov. 82 Cemented 4675' of 9-5/8" casing in 12 1/4" hole with 915 sx class "C" lite Poz. Circ cmt to 400'. W.O.C. 20 1/4 hrs. Test to 1000#, no leaks.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Clyde A. Adcock, Jr.

SIGNED Clyde A. Adcock, Jr. TITLE Drilling Engineer DATE March 28, 1983

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE MAR 6 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 5 1983

C.C.D.  
HOBBS OFFICE