

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
E-6426

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Aztec Oil & Gas Company	8. Farm or Lease Name AW
3. Address of Operator Box 847, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER K , 2310' FEET FROM THE W LINE AND 1650 FEET FROM THE S LINE, SECTION 28 TOWNSHIP 15-S RANGE 32-E NMPM.	10. Field and Pool, or Wildcat N. Anderson Ranch
15. Elevation (Show whether DF, RT, GR, etc.) 4309 GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Spot a 25 sk plug to cover perforations from 9790-96' & 9563-69'.
2. Load hole with mud-laden fluid.
3. Spot a 25 sk plug at stub of 4½" casing.
4. If 8000' of casing is recovered, the following plugs will be spotted:
25 sx @ 7585' (Abo); 25 sx @ 6940' (Tubb); 25 sx @ 5715' (Glorieta);
25 sx @ 4050' (San Andres, which is also base of 8-5/8" casing).
5. 25 sk plug at stub of 8-5/8" casing.
6. 25 sx @ 300' (base of 13-3/8" casing).
7. 10 sk plug in the top of hole and erect a 4" regulation marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *D. D. Kirk* TITLE Agent DATE 4/30/71

APPROVED BY *[Signature]* TITLE SUPERVISOR DISTRICT DATE MAY 3 1971

CONDITIONS OF APPROVAL, IF ANY:

REF P YAM

RECEIVED

RECEIVED

MAY 3 1971

OIL CONSERVATION COMM.
HOBBS, N. M.