

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 11,502 feet, and from _____ feet to _____ feet.
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing **Plugged & Abandoned 4-11**, 1961

OIL WELL: The production during the first 24 hours was None barrels of liquid of which _____% was oil; _____% was emulsion; _____% water; and _____% was sediment. A.P.I. Gravity _____

GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of liquid Hydrocarbon. Shut in Pressure _____ lbs.
 Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy..... 1614'	T. Devonian.....	T. Ojo Alamo.....	
T. Salt..... 1785'	T. Silurian.....	T. Kirtland-Fruitland.....	
B. Salt..... 2770'	T. Montoya.....	T. Farmington.....	
T. Yates..... 3730'	T. Simpson.....	T. Pictured Cliffs.....	
T. 7 Rivers.....	T. McKee.....	T. Menefee.....	
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....	
T. Permian Panrosa 3990'	T. Gr. Wash.....	T. Mancos.....	
T. San Andres..... 4480'	T. Granite.....	T. Dakota.....	
T. Glorieta..... 6070'	T.	T. Morrison.....	
T. Permian Yaso 6640'	T.	T. Penn.....	
T. Tubbs.....	T.	T.	
T. Abo..... 8046'	T.	T.	
T. Permian Kiamita Pay line 10,754	T.	T.	
T. Permian Socorro Pay line 11,396	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1614'	1614'	Red sand, shale, & gypsum				
1614	1785'	171'	Anhydrite				
1785	2770'	985'	Salt & anhydrite				
2770	3730'	960'	Dolomite, anhydrite, salt red shale & sand				
3730	3990'	260	Sand & Dolomite				
3990	4480'	490'	Dolomite & Sand				
4480	6070'	1590'	Dolomite				
6070	6640'	570'	Dolomite red & Green shale and sand				
6640	7900'	1260'	Dolomite				
7900	8046'	146'	Dolomite, anhydrite green & gray shale				
8046	8820'	774'	Dolomite, anhydrite, brown & green shale				
8820	9630'	810'	Dolomite				
9630	9828'	198'	Dolomite & limestone				
9828	10110'	282'	Limestone w/chert				
10110	10700'	590'	Dolomite, limestone, chert green & red shale				
10700	10880'	120'	Limestone				
10880	11250'	430'	Limestone, gray black & green shale				
11250	11502'	252'	Limestone				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

9-25-61

Company or Operator Midwest Oil Corporation Address 1500 Wilco Bldg., Midland, Texas
 Name W. E. Wittenburg Position or Title District Clerk