

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

Santa Fe, New Mexico

NOV 13 1953

OIL CONSERVATION COMMISSION
ORD **HOBBS-OFFICE**

DUPLICATE WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE.

The Ohio Oil Company
(Company or Operator)

J. M. Denton
(Lease)

Well No. 11, in SE 1/4 of SE 1/4, of Sec. 11, T. 15 S, R. 37 E, NMPM.

Denton-Wolfcamp

.Pool,

Loss

County.

Well is 990 feet from East line and 330 feet from South line

of Section 11 If State Land the Oil and Gas Lease No. is.....

Drilling Commenced.....**July 22,**....., 19**53**..... Drilling was Completed.....**September 9,**....., 19**53**.....

Name of Drilling Contractor..... **Company tools**

Address.....Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head..... The information given is to be kept confidential until
....., 19.....

OIL SANDS OR ZONES

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2. from to feet.

No. 3. from to feet.

No. 4. from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	48	New	350	Baker guide shoe			
9-5/8	40	New	4774	Baker float collar			
5-1/2	17 & 20	New	9296				
2-3/8	4.7	New	9175				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2	13-3/8	363	100	HOWCO		
12-1/2	9-5/8	4750	2000	"		
7-7/8	5-1/2	9313	1642	"		
	2-3/8	9199				

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforations in 5 1/2" casing 9074-9094, 9110-9155, 9176-9216.

Acidised w/500 gal. mud acid from 9074-9216 & 3000 gal. reg. acid from 9074-9216

and 450 gal. mud acid from 9074-9216 & 3000 gal. regular acid from 9074-9216.

Result of Production Stimulation.....

.....Depth Cleaned Out...../

REPORT OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from surface feet to T.D. 9315, P.B. 9273 feet, and from - feet to - feet.
Cable tools were used from - feet to - feet, and from - feet to - feet.

PRODUCTION

Put to Producing October 26, 1953

OIL WELL: The production during the first 24 hours was 60 barrels of liquid of which 100 % was
was oil; - % was emulsion; - % water; and - % was sediment. A.P.I.
Gravity 43 @ 60

GAS WELL: The production during the first 24 hours was - M.C.F. plus - barrels of
liquid Hydrocarbon. Shut in Pressure - lbs.

Length of Time Shut in -

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	T. McKee.....	T. Menefee.....
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	T. Granite.....	T. Dakota.....
T. Glorieta.....	T. <u>Wolfcamp 9050</u>	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo.....	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2811	2811	Surf. gravel, Sand, Red Beds, Shells, Gypsum & Salt.				
2811	3469	658	Red bed, anhy, salt & Gyp.				
3469	4325	856	Anhy. & Gypsum.				
4325	4753	428	Lime & Anhy.				
4753	5900	1147	Lime.				
5900	5932	32	Lime & Sand.				
5932	6968	1036	Lime.				
6968	7011	43	Lime & Dolomite.				
7011	9315	2304	Lime.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

Hobbs, New Mexico November 9, 1953
(Date)

Company or Operator The Ohio Oil Company

Address P. O. Box 2107

Name R. L. Parnell

Position or Title Superintendent