

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
-	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		7. Unit Agreement Name
2. Name of Operator Skelly Oil Company		8. Farm or Lease Name E. J. Yaden
3. Address of Operator Box 730 - Hobbs, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER "G" 1980 FEET FROM THE North LINE AND 1980 FEET FROM East LINE, SECTION 11 TOWNSHIP 16-S RANGE 37-E N.M.P.M.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3796' DF		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was drilled to a Total Depth of 5767' with no commercial quantities of oil or gas encountered in any zone. Well plugged and abandoned in the following manner:

1. Spotted cement plugs through open ended drill pipe as follows:
5767-5587' - 75 sacks cement
4800-4673' - 50 sacks cement
3000-2874' - 50 sacks cement
2. Placed 20 sack cement cap from 50' to surface and installed 4" steel dry hole marker.
3. All intervals not cemented are filled with heavy mud laden fluid.
4. Plugging operations were completed on November 28, 1946.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

(ORIGINAL SIGNED) **H. E. Aab**

SIGNED _____ TITLE **Dist. Superintendent** DATE **May 26, 1965**

APPROVED BY **Joe H. Ramirez** TITLE **Dist. Super** DATE **5/28/65**

CONDITIONS OF APPROVAL, IF ANY:

