

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. The plan will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection of the plan. The Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOP.O. Box 547, Hobbs, New Mexico
(Place)September 9, 1953
(Date)

Gentlemen:

Monticelli "34"

Following is a Notice of Intention to do certain work as described below at the

Tide Water Associated Oil Company

(Company or Operator)

1-A E

Well No. in (Unit)

SW 1/4 NW 1/4 of Sec. 20, T-16-S, R-37-E, NMPM, East Lovington (Penn) Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The above well has been drilled to a total depth of 11,465' and no oil or gas in commercial quantities was encountered while penetrating the well to this depth. A string of 13-3/8" OD. surface casing was set and cemented at 292' with 425 sacks of cement; the cement circulated to the surface. A string of 8-5/8" OD. casing was set at 4987' and cemented with 2300 sacks of cement; the cement circulated.

The hole has been circulated to total depth with mud-laden fluid preparatory to plugging. We propose to run a cement plug in the open hole above the objective horizon, Pennsylvanian Strawn, from 11,316-11,205' and a plug in the bottom of the 8-5/8" casing from 4987-4875'. A plug (15 sacks) will be set in the top of the surface casing and a 4" OD. steel marker will be cemented to extend 4' above the mean ground level.

Form C-105, Well Record, accompanies this notice.

Orig., 2 copies - OCC copies - Sohio Oil Company Montoya Oil Company
4 copies - TGA Skelly Oil Company Western Natural Gas Company
Tide Water Associated Oil Company

Approved..... SEP 11 1953
Except as follows:....., 19.....

By *H.E. Wendt* Company or Operator
H.P. Shackelford
Position..... District Foreman
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By *J. Stanley*
Engineer District I
Title.....

Name..... H.P. Shackelford
Address..... P.O. Box 547, Hobbs, New Mexico

