

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE

MISCELLANEOUS NOTICES

AUG 27 1945

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Midland, Texas, August 21, 1945

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

The Texas Company's J. S. Eaves Well No. 1 in SE 1/4 NE 1/4
Company or Operator Lease
of Sec. 26, T. 16-S, R. 38-E, N. M. P. M., Wildecat Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

This well has been drilled to total depth of 10,085', encountering sulfur water from 8845' to 8975', and no effective porosity below 9150'. We propose to salvage, plug and abandon as follows. Hole will be filled with heavy mud and the following cement plugs will be spotted: 30 sacks, 9300'-9170'; 30 sacks, 8800'-8670'; 30 sacks, 6550'-6420'; and 30 sacks in bottom of 7" casing from 5250' to 5100'. Part and pull all possible (approximately 3300') of 7" casing and spot a 30-sack cement plug in top of parted 7" casing (from approximately 3350' to 3250'). Spot a cement plug of 40 sacks in bottom of 9-5/8" casing from approximately 2220' to 2120'. Part and pull all possible (approximately 1500') of 9-5/8" casing, and spot a cement plug of 30 sacks in the top of the parted 9-5/8" casing. Spot a 40-sack cement plug in the bottom of the 13-3/8" casing, from approximately 340' to 290'. The customary 4" pipe marker will be cemented in the top of the hole with 20 sacks, leaving all 13-3/8" casing cemented in the hole. All mud and cement will be pumped in through tubing or drill pipe.

Approved AUG 27 1945, 19____
except as follows:

THE TEXAS COMPANY

Company or Operator

By [Signature]

Position Drilg. & Prod. Foreman

Send communications regarding well to

Name The Texas Company

Address Box 1270

Midland, Texas

OIL CONSERVATION COMMISSION,

By [Signature]

Title Oil & Gas Inspector